

AS-INTERFACE F-ADAPTER FOR EMERG. STOP ACTUATOR
3SB3, SCREW CONNECTION, 2I/1O, OUTPUT FOR LED
CONTROL

Product designation	AS-Interface F-adapter for EMERGENCY-OFF control device SIRIUS 3SB3
General technical data	
Protection class IP	IP20
Equipment marking	
• acc. to DIN EN 61346-2	S
• acc. to DIN EN 81346-2	S
Connections/Terminals	
Type of electrical connection	
• for auxiliary and control current circuit	screw-type terminals
Safety related data	
Safety Integrity Level (SIL) acc. to IEC 61508	SIL3
Ambient conditions	
Ambient temperature	
• during operation	-25 ... +70 °C
Inputs/ Outputs	
Number of digital inputs	2
• safety-related	2
Number of digital outputs	1
Installation/ mounting/ dimensions	
Mounting type	front mounting
Height	61 mm
Width	30 mm
Depth	52 mm
Certificates/approvals	

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity	Test Certificates	other
--------------------------	---------------------------------------	---------------------------	-------------------	-------



[sonstig](#)



[spezielle
Prüfbescheinigunge
n](#)



other

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SF5402-1AB03>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SF5402-1AB03>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SF5402-1AB03>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SF5402-1AB03&lang=en

last modified:

10/17/2016