

COMPONENT FOR AS-I ENCLOSURE PLASTIC ENCLOSURE
WITHOUT PROTECTIVE COLLAR AS-I F-SLAVE 2 SAFE INPUTS
FOR 1-6 COMMAND POSITIONS

Product designation	F-slave
General technical data	
Protection class IP	IP20
Equipment marking	
• acc. to DIN EN 61346-2	K
• acc. to DIN EN 81346-2	K
Safety related data	
Safety Integrity Level (SIL) acc. to IEC 61508	SIL3
Ambient conditions	
Ambient temperature	
• during operation	-25 ... +70 °C
Inputs/ Outputs	
Number of digital inputs	2
• safety-related	2
Number of digital outputs	0
Installation/ mounting/ dimensions	
Mounting type	floor mounting
Height	71 mm
Width	17.6 mm
Depth	50.1 mm
Certificates/approvals	

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity	Shipping Approval
--------------------------	---------------------------------------	---------------------------	-------------------



[sonstig](#)



Shipping Approval	other
-------------------	-------



[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SF5500-0BA>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SF5500-0BA>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SF5500-0BA>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SF5500-0BA&lang=en

last modified:

10/17/2016