

COMPONENT FOR AS-I ENCLOSURE PLASTIC ENCLOSURE AS-I A/B SLAVE 4 INPUTS/3 OUTPUTS FOR 2-6 COMMAND POSITIONS



Product designation	A/B-Slave
General technical data	
Protection class IP	IP20
Equipment marking	
• acc. to DIN EN 61346-2	K
• acc. to DIN EN 81346-2	K
Ambient conditions	
Ambient temperature	
• during operation	-25 ... +70 °C
Inputs/ Outputs	
Number of digital inputs	4
• safety-related	0
Number of digital outputs	3
Installation/ mounting/ dimensions	
Mounting type	floor mounting
Height	71 mm
Width	22.1 mm
Depth	50.1 mm

Certificates/approvals

General Product Approval		Functional Safety/Safety of Machinery	Declaration of Conformity	Shipping Approval
 TUV	 UL		sonstig EG-Konf.	 ABS

Shipping Approval		other	
			
DNV	LRS	PRS	Asi

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SF5500-0BB>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SF5500-0BB>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SF5500-0BB>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SF5500-0BB&lang=en

last modified:

09/15/2016