

COMPONENT FOR AS-I ENCLOSURE PLASTIC ENCLOSURE AS-I SLAVE 4 INPUTS/4 OUTPUTS FOR 2-6 COMMAND POSITIONS



Figure similar

Product designation	Slave
General technical data	
Protection class IP	IP20
Equipment marking	
• acc. to DIN EN 61346-2	K
• acc. to DIN EN 81346-2	K
Ambient conditions	
Ambient temperature	
• during operation	-25 ... +70 °C
Inputs/ Outputs	
Number of digital inputs	4
• safety-related	0
Number of digital outputs	4
Installation/ mounting/ dimensions	
Mounting type	floor mounting
Height	71 mm

Width	22.1 mm
Depth	50.1 mm

Certificates/approvals

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity	Shipping Approval
--------------------------	---------------------------------------	---------------------------	-------------------



TUV



UL



[sonstig](#)



EG-Konf.



ABS

Shipping Approval	other
-------------------	-------



DNV



LRS



PRS



ASi

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SF5500-0BC>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SF5500-0BC>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SF5500-0BC>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SF5500-0BC&lang=en

last modified:

10/07/2016