

ENCLOSED PUSHBUTTON; ENCLOSURE IN METAL VERSION
B=INDICATOR LIGHT YELLOW A=PUSHBUTTON BLACK, 1S M12
CONNECTOR FOR AS-INTERFACE CONNECTION;SLAVE 4E/4A;
CUSTOMER-SPECIFIC VANDERLANDE

Enclosure:	
Design of the housing	AS-Interface enclosure with standard equipment
Shape of the enclosure front	rectangular
Material of the enclosure	metal
Number of command points	2
Product component	
• protective collar	No
Color	
• of top part of the enclosure	grey
Delivery state	
• pre-wired on strip terminal	Yes
Mounting type of the enclosure	Vertical

Actuator:	
Design of the operating mechanism	Pushbutton / indicator light
Product extension optional Light source	No
Color	
• of the actuating element	A = black / B = yellow
Material of the actuating element	plastic
Type of unlocking device	without

Front ring:	
Product component front ring	Yes
Material of the front ring	metal
Color of the front ring	silver

Holder:	
Material of the holder	Metal

Contact block/ lampholder:	
Mounting type	integrated LED
Number of lampholders	1
Number of switching elements	1

General technical data:	
Product function	
• positive opening	No

• EMERGENCY OFF function	No
• EMERGENCY STOP function	No
Product component	
• Light source	Yes
Type of voltage	
• of the operating voltage	DC
Protection class IP	IP67
Vibration resistance	
• acc. to IEC 60068-2-6	20 ... 200 Hz: 5g
Equipment marking	
• acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	S
• acc. to DIN EN 61346-2	S
• acc. to DIN EN 81346-2	S
Operating voltage	
• at DC	
— rated value	26.5 ... 31.5 V
Operating voltage 1	
• at DC rated value	30 V

Supply voltage:

Type of voltage of the supply voltage	
• of the light source	AC/DC

Auxiliary circuit:

Number of NC contacts	
• for auxiliary contacts	0
Number of NO contacts	
• for auxiliary contacts	1
Number of CO contacts	
• for auxiliary contacts	0

Connections/ Terminals:

Type of electrical connection on enclosure	M12 connector, 4-pole, bottom
Tightening torque of the screws in the bracket	1.4 ... 1.6 N·m

Ambient conditions:

Ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C

Installation/ mounting/ dimensions:

Mounting type	
• of contact blocks, socket, and accessories	Floor mounting
• of AS-i slaves	Floor mounting

Height	114 mm
Width	85 mm
Depth	65 mm
Shape of the installation opening	round
Mounting diameter	22 mm

Measuring circuit:

Product function	miscellaneous
------------------	---------------

Accessories:

Number of labels	0
Number of backing plates	0

Certificates/approvals

General Product Approval	Functional Safety/Safety of Machinery	other
--------------------------	---------------------------------------	-------



[sonstig](#)



[sonstig](#)

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SF5812-2DG10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SF5812-2DG10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SF5812-2DG10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SF5812-2DG10&lang=en

last modified:

10/07/2016