



AS-INTERFACE ENCLOSURE FOR COMMAND DEVICES, 22MM, ROUND, ENCLOSURE MATERIAL PLASTIC, GRAY ENCLOSURE TOP PART, 3 COMMAND POINTS, C=CLEAR INDICATOR LIGHT, LED 24V, LABEL WITHOUT INSCRIPTION, B=WHITE PUSHBUTTON, 1NO, LABEL: I, A=BLACK PUSHBUTTON, 1NO, LABEL: O, CABLE ENTRY FOR SHAPED CABLE ON TOP

Enclosure:

Design of the housing	AS-Interface enclosure with standard equipment
Shape of the enclosure front	rectangular
Material of the enclosure	plastic
Number of command points	3
Product component	
• protective collar	No
Color	
• of top part of the enclosure	grey
Delivery state	
• pre-wired on strip terminal	Yes
Mounting type of the enclosure	Vertical

Actuator:

Design of the operating mechanism	Pushbutton / indicator light
Product extension optional Light source	No
Color	
• of the actuating element	A = black / B = white / C = clear
Material of the actuating element	plastic

Type of unlocking device	without
Front ring:	
Product component front ring	Yes
Material of the front ring	plastic
Color of the front ring	black
Holder:	
Material of the holder	Plastic
Contact block/ lampholder:	
Mounting type	integrated LED
Number of lampholders	1
Number of switching elements	2
General technical data:	
Product function	
• positive opening	No
• EMERGENCY OFF function	No
• EMERGENCY STOP function	No
Product component	
• Light source	Yes
Type of voltage	
• of the operating voltage	DC
Protection class IP	IP65
Vibration resistance	
• acc. to IEC 60068-2-6	20 ... 200 Hz: 5g
Equipment marking	
• acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	S
• acc. to DIN EN 61346-2	S
• acc. to DIN EN 81346-2	S
Operating voltage	
• at DC	
— rated value	26.5 ... 31.5 V
Operating voltage 1	
• at DC rated value	30 V
Supply voltage:	
Type of voltage of the supply voltage	
• of the light source	AC/DC
Auxiliary circuit:	
Number of NC contacts	
• for auxiliary contacts	0
Number of NO contacts	

• for auxiliary contacts	2
Number of CO contacts	
• for auxiliary contacts	0

Connections/ Terminals:

Type of electrical connection on enclosure	With insulation-displacement terminal, top
Tightening torque of the screws in the bracket	1 ... 1.2 N·m

Ambient conditions:

Ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C

Installation/ mounting/ dimensions:

Mounting type	
• of contact blocks, socket, and accessories	Floor mounting
• of AS-i slaves	Floor mounting
Height	154 mm
Width	85 mm
Depth	64 mm
Shape of the installation opening	round
Mounting diameter	22 mm

Measuring circuit:

Product function	miscellaneous
-------------------------	---------------

Accessories:

Number of labels	3
Marking of the name plate for command devices	A = O / B = I
Color of the label	Black
Number of backing plates	0

Certificates/approvals

General Product Approval	Functional Safety/Safety of Machinery	other
---------------------------------	--	--------------



[sonstig](#)



[sonstig](#)

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SF5813-0DC00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SF5813-0DC00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SF5813-0DC00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SF5813-0DC00&lang=en

last modified:

10/07/2016