

AS-I ENCLOSURE, 22MM PROGRAM 3 COMMAND POSITIONS
METAL VERSION A=PUSHBUTTON BLACK, LABEL O
B=PUSHBUTTON WHITE, LABEL I C=INDIC.LIGHT CLEAR,ONLY LABEL



Figure similar

Enclosure:	
Design of the housing	AS-Interface enclosure with standard equipment
Shape of the enclosure front	rectangular
Material of the enclosure	metal
Number of command points	3
Product component	
• protective collar	No
Color	
• of top part of the enclosure	grey
Delivery state	
• pre-wired on strip terminal	Yes
Mounting type of the enclosure	Vertical
Actuator:	
Design of the operating mechanism	Pushbutton / indicator light
Product extension optional Light source	No
Color	
• of the actuating element	A = black / B = white / C = clear

Material of the actuating element	plastic
Type of unlocking device	without
Front ring:	
Product component front ring	Yes
Material of the front ring	metal
Color of the front ring	silver
Holder:	
Material of the holder	Metal
Contact block/ lampholder:	
Mounting type	integrated LED
Number of lampholders	1
Number of switching elements	2
General technical data:	
Product function	
• positive opening	No
• EMERGENCY OFF function	No
• EMERGENCY STOP function	No
Product component	
• Light source	Yes
Type of voltage	
• of the operating voltage	DC
Protection class IP	IP67
Vibration resistance	
• acc. to IEC 60068-2-6	20 ... 200 Hz: 5g
Equipment marking	
• acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	S
• acc. to DIN EN 61346-2	S
• acc. to DIN EN 81346-2	S
Operating voltage	
• at DC	
— rated value	26.5 ... 31.5 V
Operating voltage 1	
• at DC rated value	30 V
Supply voltage:	
Type of voltage of the supply voltage	
• of the light source	AC/DC
Auxiliary circuit:	
Number of NC contacts	
• for auxiliary contacts	0

Number of NO contacts • for auxiliary contacts	2
Number of CO contacts • for auxiliary contacts	0

Connections/ Terminals:

Type of electrical connection on enclosure	Cable gland, top
Tightening torque of the screws in the bracket	1.4 ... 1.6 N·m

Ambient conditions:

Ambient temperature • during operation • during storage	-25 ... +70 °C -40 ... +80 °C
--	----------------------------------

Installation/ mounting/ dimensions:

Mounting type • of contact blocks, socket, and accessories • of AS-i slaves	Floor mounting Floor mounting
Height	154 mm
Width	85 mm
Depth	65 mm
Shape of the installation opening	round
Mounting diameter	22 mm

Measuring circuit:

Product function	miscellaneous
-------------------------	---------------

Accessories:

Number of labels	3
Marking of the name plate for command devices	A = O / B = I
Color of the label	Black
Number of backing plates	0

Certificates/approvals

General Product Approval	Functional Safety/Safety of Machinery	other
---------------------------------	--	--------------



[sonstig](#)



[sonstig](#)

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SF5813-2DC00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SF5813-2DC00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SF5813-2DC00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SF5813-2DC00&lang=en

last modified:

10/07/2016