

starter kit PROFINET for 3SK2 content: basic unit 3SK2 45 mm PROFINET interface connecting cable RJ45 cable Safety ES V17 Professional



product brand name	SIRIUS
product category	Safety relay
product designation	PROFINET starter kit
design of the product	comprises 3SK2122-2AA10 basic unit, PROFINET 3SK2511-2FA10 interface module, SIRIUS Safety Professional TIA and required cables
suitability for use for monitoring of optoelectronic protective devices according to IEC 61496-1	Yes
suitability for use • monitoring of floating sensors • monitoring of non-floating sensors • position switch monitoring • EMERGENCY-OFF circuit monitoring • valve monitoring • opto-electronic protection device monitoring • magnetically operated switch monitoring • proximity switch monitoring • safety-related circuits	Yes Yes Yes Yes Yes Yes Yes Yes Yes
General technical data	
product function • EMERGENCY STOP function • protective door monitoring • protective door monitoring with tumbler • muting, 2 sensor-parallel • muting, 4 sensor-parallel • muting, 4 sensor-sequential • monitoring parameterizable • evaluation: electro-sensitive protective equipment • evaluation: selector switch • pressure-sensitive mat monitoring • evaluation: two-hand operator panel • evaluation: enabling switch • monitored start-up • two-hand control according to EN 574	Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes
configuration software required	Yes; Safety ES V1.0 and higher
number of function blocks typical	50
insulation voltage rated value	50 V
degree of pollution	3
surge voltage resistance rated value	800 V
protection class IP • of the enclosure • of the terminal	IP20 IP20 IP20

shock resistance	15g / 11 ms
operating frequency maximum	2 000 1/h
reference code according to IEC 81346-2	F
Substance Prohibitance (Date)	07/01/2006
SVHC substance name	Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7 Lead titanium zirconium oxide - 12626-81-2
product function suitable for AS-i Power24V	No
product function diagnostics with CTT2 slave	No
Ambient conditions	
installation altitude at height above sea level maximum	4 000 m; Derating, see Product Notification 109792701
ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
relative humidity during operation	10 ... 95 %
air pressure according to SN 31205	90 ... 106 kPa
Electromagnetic compatibility	
EMC emitted interference according to IEC 60947-1	class A
conducted interference	
• due to burst according to IEC 61000-4-4	2 kV (power ports) / 1 kV (signal ports)
field-based interference according to IEC 61000-4-3	10 V/m
electrostatic discharge according to IEC 61000-4-2	4 kV contact discharge / 8 kV air discharge
Safety related data	
diagnostics test interval by internal test function maximum	1 000 s
stop category according to IEC 60204-1	0 / 1
IEC 62061	
SIL Claim Limit (subsystem) according to EN 62061	3
PFHD with high demand rate	
• according to IEC 62061	1.2E-8 1/h
ISO 13849	
category according to EN ISO 13849-1	4
performance level (PL) according to ISO 13849-1	e
IEC 61508	
Safety Integrity Level (SIL) according to IEC 61508	3
PFDavg with low demand rate according to IEC 61508	1.8E-5
hardware fault tolerance according to IEC 61508	1
T1 value for proof test interval or service life according to IEC 61508	20 a
Electrical Safety	
touch protection against electrical shock	finger-safe
Inputs/ Outputs	
product function	
• parameterizable inputs	Yes
• parameterizable outputs	Yes
• at the digital outputs short-circuit protection	Yes
number of inputs	
• safety-related	20
• non-safety-related	0
input delay time	0 ... 150 ms
type of digital inputs according to IEC 60947-1	Type 1
ingress acquisition time at digital input maximum	60 ms
input delay time at digital input maximum	150 ms
input voltage at digital input	
• at DC rated value	24 V
• with signal <0> at DC	-3 ... +5 V
• for signal <1> at DC	15 ... 30
input current at digital input	
• for signal <1> typical	2.6 mA
number of outputs	
• safety-related 2-channel	4

• for testing contact-based sensors	4		
number of outputs as contact-affected switching element safety-related			
• 1-channel	0		
• 2-channel	0		
number of outputs as contact-less semiconductor switching element			
• safety-related 2-channel	4		
• non-safety-related	2		
design of the contactless switching element safety-related	P potential		
recovery time of the safe outputs	0 ms		
readback time maximum	400 ms		
light test period	3 ms		
dark period of the common drivers	3 ms		
switching capacity current of semiconductor outputs at DC-13 at 24 V	4 A		
residual current			
• maximum	0.1 mA		
• at digital output with signal <0> maximum	0.1 mA		
total current maximum	7 A		
wire length of the signal cable			
• to the inputs — shielded maximum — unshielded maximum	1 000 m 600 m		
• to the outputs — shielded maximum — unshielded maximum	1 000 m 600 m		
Communication/ Protocol			
protocol optional is supported			
• PROFIBUS DP protocol	Yes; when using the DP interface module; 64 bit cyclical data		
• PROFINET IO protocol	Yes; when using the PN interface module; 64-bit cyclic data		
protocol is supported AS-Interface protocol	No		
Control circuit/ Control			
type of voltage	DC		
control supply voltage rated value	24 V		
inrush current peak			
• at 24 V	11 A		
duration of inrush current peak			
• at 24 V	1 ms		
operating power rated value	4.5 W		
Installation/ mounting/ dimensions			
mounting position	any		
fastening method	Snap-mounted to DIN rail or screw-mounted with additional push-in lug		
height	100 mm		
width	45 mm		
depth	124.5 mm		
Connections/ Terminals			
product function removable terminal	Yes		
type of electrical connection	spring-loaded terminal (push-in)		
type of connectable conductor cross-sections			
• solid	1x (0.5 ... 1.5 mm ²), 2x (0.5 ... 1.5 mm ²)		
• finely stranded with core end processing	1x (0.5 ... 1.0 mm ²), 2x (0.5 ... 1.0 mm ²)		
• for AWG cables solid	1x (20 ... 16), 2x (20 ... 16)		
• for AWG cables stranded	1x (20 ... 16), 2x (20 ... 16)		
connectable conductor cross-section finely stranded with core end processing	0.5 ... 1 mm ²		
AWG number as coded connectable conductor cross section			
• solid	20 ... 16		
• stranded	20 ... 16		
Approvals Certificates			
<table> <tr> <td>General Product Approval</td><td>Functional Safety</td></tr> </table>		General Product Approval	Functional Safety
General Product Approval	Functional Safety		

[Confirmation](#)



[Type Examination Certificate](#)

other

Environment

[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SK2942-2AA11>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SK2942-2AA11>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SK2942-2AA11>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SK2942-2AA11&lang=en

last modified:

3/11/2024