# **SIEMENS**

### **Data sheet**

## 3SU1000-1AA10-0AA0



Mushroom pushbutton, 22 mm, round, plastic, black, 30 mm, latching, Pull-to-unlatch mechanism

product brand name product designation design of the product product type designation product line SIRIUS ACT Mushroom pushbuttons Actuating/signaling element 3SU1

Plastic, black, 22 mm

number of command points

Actuator

principle of operation of the actuating element product extension optional light source

No

product extension optional light source

color of the actuating element

material of the actuating element

shape of the actuating element

outer diameter of the actuating element

type of unlocking device

No

black

plastic

round

30 mm

type of unlocking device

number of switching positions

round
30 mm
pull-to-unlatch mechanism
2

Front ring

product component front ring
design of the front ring
material of the front ring
color of the front ring

Yes Standard plastic black

General technical data

product functionEMERGENCY OFF function

• EMERGENCY STOP function

protection class IP

degree of protection NEMA rating shock resistance

according to IEC 60068-2-27

• for railway applications according to EN 61373

vibration resistance

• according to IEC 60068-2-6

• for railway applications according to EN 61373

operating frequency maximum

mechanical service life (switching cycles) typical reference code according to IEC 81346-2

**Substance Prohibitance (Date)** 

No

IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13

sinusoidal half-wave 15g / 11 ms

Category 1, Class B

10 ... 500 Hz: 5g Category 1, Class B 1 800 1/h

500 000 S

10/01/2014

**Ambient conditions** 

ambient temperature

during operationduring storage

-25 ... +70 °C

-40 ... +80 °C

environmental category during operation according to IEC 60721

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%)

# Installation/ mounting/ dimensions

height 30 mm width 30 mm shape of the installation opening round mounting diameter 22.3 mm positive tolerance of installation diameter 0.4 mm mounting height 27.5 mm installation width 30 mm installation depth 24.4 mm

# Certificates/ approvals

#### **General Product Approval**

**Declaration of Conformity** 



Confirmation









**Test Certificates** 

Marine / Shipping

Special Test Certificate

Type Test Certificates/Test Report









Marine / Shipping

other



Environmental Confirmations

Confirmation

#### **Further information**

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1000-1AA10-0AA0


Cax online generator


http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1000-1AA10-0AA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1000-1AA10-0AA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1000-1AA10-0AA0&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1000-1AA10-0AA0&lang=en</a>





last modified: 1/27/2022 🖸