



Mushroom pushbutton, 22 mm, round, plastic, blue, 40 mm, positive latching, acc. to EN ISO 13850, rotate-to-unlatch, with laser labeling, upper case and lower case, always upper case at the beginning of the word

|                                                    |                                                                                               |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------|
| product brand name                                 | SIRIUS ACT                                                                                    |
| product designation                                | Mushroom pushbuttons                                                                          |
| design of the product                              | Actuating/signaling element                                                                   |
| product type designation                           | 3SU1                                                                                          |
| product line                                       | Plastic, black, 22 mm                                                                         |
| Enclosure                                          |                                                                                               |
| number of command points                           | 1                                                                                             |
| Actuator                                           |                                                                                               |
| design of the actuating element                    | positive latching                                                                             |
| principle of operation of the actuating element    | latching                                                                                      |
| product extension optional light source            | No                                                                                            |
| color of the actuating element                     | blue                                                                                          |
| material of the actuating element                  | plastic                                                                                       |
| shape of the actuating element                     | round                                                                                         |
| outer diameter of the actuating element            | 40 mm                                                                                         |
| marking of the actuating element                   | Customized labeling, text in lower case/capital letters, all words start with capital letters |
| type of unlocking device                           | rotate-to-unlatch mechanism                                                                   |
| number of switching positions                      | 2                                                                                             |
| Front ring                                         |                                                                                               |
| product component front ring                       | No                                                                                            |
| design of the front ring                           | without                                                                                       |
| General technical data                             |                                                                                               |
| product function                                   |                                                                                               |
| • EMERGENCY OFF function                           | No                                                                                            |
| • EMERGENCY STOP function                          | No                                                                                            |
| protection class IP                                | IP66, IP67, IP69(IP69K)                                                                       |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13                                                                    |
| shock resistance                                   |                                                                                               |
| • according to IEC 60068-2-27                      | sinusoidal half-wave 15g / 11 ms                                                              |
| • for railway applications according to EN 61373   | Category 1, Class B                                                                           |
| vibration resistance                               |                                                                                               |
| • according to IEC 60068-2-6                       | 10 ... 500 Hz: 5g                                                                             |
| • for railway applications according to EN 61373   | Category 1, Class B                                                                           |
| operating frequency maximum                        | 600 1/h                                                                                       |
| mechanical service life (operating cycles) typical | 300 000                                                                                       |
| reference code according to IEC 81346-2            | S                                                                                             |

|                                                                         |                                                                    |
|-------------------------------------------------------------------------|--------------------------------------------------------------------|
| Substance Prohibittance (Date)                                          | 10/01/2014                                                         |
| Weight                                                                  | 0.037 kg                                                           |
| <b>Safety related data</b>                                              |                                                                    |
| proportion of dangerous failures                                        |                                                                    |
| • with low demand rate according to SN 31920                            | 20 %                                                               |
| • with high demand rate according to SN 31920                           | 20 %                                                               |
| B10 value with high demand rate according to SN 31920                   | 100 000                                                            |
| failure rate [FIT] with low demand rate according to SN 31920           | 100 FIT                                                            |
| IEC 61508                                                               |                                                                    |
| T1 value for proof test interval or service life according to IEC 61508 | 20 a                                                               |
| <b>Ambient conditions</b>                                               |                                                                    |
| ambient temperature                                                     |                                                                    |
| • during operation                                                      | -25 ... +70 °C                                                     |
| • during storage                                                        | -40 ... +80 °C                                                     |
| environmental category during operation according to IEC 60721          | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| <b>Environmental footprint</b>                                          |                                                                    |
| Environmental Product Declaration (EPD)                                 | Yes                                                                |
| Global Warming Potential [CO2 eq] total                                 | 0.787 kg                                                           |
| Global Warming Potential [CO2 eq] during manufacturing                  | 0.566 kg                                                           |
| Global Warming Potential [CO2 eq] during operation                      | 0.235 kg                                                           |
| Global Warming Potential [CO2 eq] after end of life                     | -0.015 kg                                                          |
| Siemens Eco Profile (SEP)                                               | Siemens EcoTech                                                    |
| <b>Installation/ mounting/ dimensions</b>                               |                                                                    |
| height                                                                  | 40 mm                                                              |
| width                                                                   | 40 mm                                                              |
| shape of the installation opening                                       | round                                                              |
| mounting diameter                                                       | 22.3 mm                                                            |
| positive tolerance of installation diameter                             | 0.4 mm                                                             |
| mounting height                                                         | 45.3 mm                                                            |
| installation width                                                      | 40 mm                                                              |
| installation depth                                                      | 26.3 mm                                                            |
| <b>Approvals Certificates</b>                                           |                                                                    |
| General Product Approval                                                |                                                                    |
| Test Certificates                                                       |                                                                    |



[Confirmation](#)



[Type Test Certificates/Test Report](#)

Test Certificates

other

Environment

[Special Test Certificate](#)

[Confirmation](#)



Siemens  
EcoTech



[Environmental Confirmations](#)

## Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1000-1HB50-0AA0-Z Y15>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1000-1HB50-0AA0-Z Y15>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1000-1HB50-0AA0-Z Y15>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1000-1HB50-0AA0-Z Y15&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1000-1HB50-0AA0-Z Y15&lang=en)

