



key-operated switch Siemens, 22 mm, round, metal, shiny, lock no. LSG1, with 2 keys, 2 switch positions O-I, latching, actuating angle 90°, 10:30h/13:30h, key removal O

|                                                    |                                    |
|----------------------------------------------------|------------------------------------|
| product brand name                                 | SIRIUS ACT                         |
| product designation                                | Key-operated switches              |
| design of the product                              | Actuating/signaling element        |
| product type designation                           | 3SU1                               |
| product line                                       | Metal, shiny, 22 mm                |
| manufacturer's article number of included key      | <a href="#">3SU1950-0FN80-0AA0</a> |
| <b>Actuator</b>                                    |                                    |
| principle of operation of the actuating element    | latching, 90° (10:30 h/13:30 h)    |
| product extension optional light source            | No                                 |
| color                                              |                                    |
| • of the actuating element                         | silver                             |
| material of the actuating element                  | metal                              |
| shape of the actuating element                     | Key                                |
| outer diameter of the actuating element            | 29.5 mm                            |
| number of switching positions                      | 2                                  |
| switch position for key distraction                | O                                  |
| actuating angle                                    |                                    |
| • clockwise                                        | 90°                                |
| lock make                                          | Siemens                            |
| key number                                         | LSG1                               |
| <b>Front ring</b>                                  |                                    |
| product component front ring                       | Yes                                |
| design of the front ring                           | Standard                           |
| material of the front ring                         | Metal, high gloss                  |
| color of the front ring                            | silver                             |
| <b>General technical data</b>                      |                                    |
| protection class IP                                | IP66, IP67, IP69(IP69K)            |
| • of the terminal                                  | IP20                               |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13         |
| shock resistance                                   |                                    |
| • acc. to IEC 60068-2-27                           | sinusoidal half-wave 15g / 11 ms   |
| vibration resistance                               |                                    |
| • acc. to IEC 60068-2-6                            | 10 ... 500 Hz: 5g                  |
| operating frequency maximum                        | 1 800 1/h                          |
| mechanical service life (switching cycles) typical | 300 000                            |
| reference code acc. to IEC 81346-2                 | S                                  |
| Substance Prohibitance (Date)                      | 01.10.2014                         |
| <b>Ambient conditions</b>                          |                                    |
| ambient temperature                                |                                    |

- during operation
- during storage

-25 ... +70 °C

-40 ... +80 °C

environmental category during operation acc. to IEC 60721

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%)

#### Installation/ mounting/ dimensions

|                                             |         |
|---------------------------------------------|---------|
| height                                      | 29.5 mm |
| width                                       | 29.5 mm |
| shape of the installation opening           | round   |
| mounting diameter                           | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm  |
| mounting height                             | 61 mm   |
| installation width                          | 29.5 mm |
| installation depth                          | 25.4 mm |

#### Certificates/ approvals

General Product Approval

Declaration of Conformity

Test Certificates



[UK Declaration of Conformity](#)

[Special Test Certificate](#)

Test Certificates

Marine / Shipping

[Type Test Certificates/Test Report](#)



other

[Confirmation](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-5HF01-0AA0>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-5HF01-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-5HF01-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1050-5HF01-0AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-5HF01-0AA0&lang=en)



last modified:

1/26/2022 