

ENCLOSURE FOR 4-POSITION SELECTOR SWITCH, COORDINATE SWITCH, ID KEY SWITCH AND SENSOR SWITCH, 22 MM, ROUND, ENCLOSURE MATERIAL PLASTIC, ENCLOSURE TOP PART GRAY, 1 COMMAND POINT PLASTIC, UNEQUIPPED



Figure similar

| | |
|----------------------------------|-----------------------------|
| Product brand name | SIRIUS ACT |
| Product designation | Enclosures |
| Product type designation | 3SU1 |
| Enclosure | |
| Design of the housing | Command point in center |
| Shape of the enclosure front | Square |
| Material of the enclosure | plastic |
| Number of command points | 1 |
| Product component | |
| • protective collar | No |
| Color | |
| • of top part of the enclosure | grey |
| Mounting type of the enclosure | Vertical / horizontal |
| General technical data | |
| Protection class IP | IP66, IP67, IP69(IP69K) |
| Degree of protection NEMA rating | NEMA 1, 2, 3, 3R, 4, 4X, 12 |
| Shock resistance | |

| | |
|---|---------------------|
| • for railway applications acc. to DIN EN 61373 | Category 1, Class B |
| Vibration resistance | |
| • for railway applications acc. to DIN EN 61373 | Category 1, Class B |

Mechanical data

| | |
|-------------------------|---------|
| Cable entry type | Without |
|-------------------------|---------|

Connections/Terminals

| | |
|--|---|
| Type of electrical connection on enclosure | Cable routing above and below, both 1 x M20 |
| Tightening torque of mounting screws in the enclosure cover | 1.5 ... 1.7 N·m |

Ambient conditions

| | |
|----------------------------|----------------|
| Ambient temperature | |
| • during operation | -25 ... +70 °C |
| • during storage | -40 ... +80 °C |

Installation/ mounting/ dimensions

| | |
|--|----------------------|
| Mounting type | |
| • of modules and accessories | Front plate mounting |
| Height | 85 mm |
| Width | 85 mm |
| Depth | 68 mm |
| Mounting diameter | 22.3 mm |
| Positive tolerance of installation diameter | 0.4 mm |

Certificates/approvals

| | |
|--|---|
| General Product Approval | Declaration of Conformity |
|  CCC |  CSA |
|  UL |  VDE |
|  EAC |  EG-Konf. |

| | |
|--|--|
| Test Certificates | other |
| Declaration of the Compliance with the order | Special Test Certificate |
| | Confirmation |

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1801-1AA00-1AA1>


Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1801-1AA00-1AA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1801-1AA00-1AA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1801-1AA00-1AA1&lang=en



last modified:

09/25/2017