SIEMENS

Product data sheet 3TB5617-0LB4

CONTACTOR SIZE 12 3-POLE DC-3 AND 5, 400 A AT 750V AUXILIARY CONTACTS 21 (2NO+1NC) SETTING RANGE 0.7 TO 1.25X US SWITCHED WITH VARISTOR DC OPERATION DC SOLENOID SYSTEM DC 24V

| General details: | | | | |
|---|----|-----------------|--|--|
| Size of the contactor | | 12 | | |
| Protection class IP / on the front | | IP00 | | |
| Ambient temperature | | | | |
| during operating | °C | -50 +7 0 | | |
| Reference code | | | | |
| according to DIN 40719 extended according to IEC 204-2 / according to IEC 750 | | К | | |
| according to DIN EN 61346-2 | | Q | | |
| Number of poles / for main current circuit | | 3 | | |
| Operating current / at AC-1 / at 400 V | | | | |
| • at 40 °C ambient temperature / rated value | Α | 425 | | |
| • at 60 °C ambient temperature / rated value | А | 400 | | |
| Impulse voltage resistance / rated value | kV | 8 | | |
| Main circuit: | | | | |
| Number of NC contacts / for main contacts | | 0 | | |
| Number of NO contacts / for main contacts | | 3 | | |
| Operating current / at AC-3 / at 400 V / rated value | Α | 400 | | |
| Service power | | | | |
| • at AC-3 / at 400 V / rated value | kW | 200 | | |
| • at AC-1 / at 400 V / rated value | kW | 262 | | |
| Control circuit: | | | | |
| Design of activation / of the operating mechanism | | conventional | | |
| Design of the surge suppressor | | with varistor | | |
| Voltage type / of control feed voltage | | DC | | |
| Control supply voltage | | | | |
| • for DC / rated value | V | 24 | | |
| Auxiliary circuit: | | | | |
| Number of NC contacts / for auxiliary contacts | | | | |

| 1 |
|---|
| |
| |
| 0 |
| 2 |
| - |

| Connection type: | | |
|---|----------------------|--|
| Design of the electrical connection | | |
| for main current circuit | screw-type terminals | |
| for auxiliary and control current circuit | screw-type terminals | |
| Identification number and letter for switching elements | 21 | |

| Mechanical design: | | |
|-------------------------------------|----|--------------|
| Mounting type | | screw fixing |
| Mounting type / series installation | | Yes |
| Width | mm | 174 |
| Height | mm | 200 |
| Depth | mm | 282 |

Certificates/approvals:

General Product Approval







Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

 $\underline{\text{http://www.siemens.com/industrial-controls/mall}}$

Cax online generator:

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3TB5617-0LB4/all

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ ...)$

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TB5617-0LB4

last change: Jun 16, 2014