SIEMENS

Product data sheet 3TB5617-0LJ8

CONTACTOR SIZE 12 3-POLE AUXILIARY CONTACTS 21 (2NO+1NC) SETTING RANGE 0.7 TO 1.25X US SWITCHED WITH VARISTOR DC OPERATION DC SOLENOID SYSTEM DC 72V

General details:		
Size of the contactor		12
Protection class IP / on the front		IP00
Ambient temperature		
during operating	°C	-50 + 70
Reference code		
 according to DIN 40719 extended according to IEC 204-2 / according to IEC 750 		К
according to DIN EN 61346-2		Q
Number of poles / for main current circuit		3
Operating current / at AC-1 / at 400 V		
 at 40 °C ambient temperature / rated value 	Α	425
• at 60 °C ambient temperature / rated value	Α	400
Impulse voltage resistance / rated value	kV	8
Main circuit:		
Number of NC contacts / for main contacts		0
Number of NO contacts / for main contacts		3
Operating current / at AC-3 / at 400 V / rated value	Α	400
Service power		
• at AC-3 / at 400 V / rated value	kW	200
• at AC-1 / at 400 V / rated value	kW	262
Control circuit:		
Design of activation / of the operating mechanism		conventional
Design of the surge suppressor		with varistor
Voltage type / of control feed voltage		DC
Control supply voltage		
• for DC / rated value	V	72
Auxiliary circuit:		
Number of NC contacts / for auxiliary contacts		
lagging switching		0

• instantaneous switching	1	
Number of NO contacts / for auxiliary contacts		
leading switching	0	
• instantaneous switching	2	

Coni	nection	type:

· ·	
Design of the electrical connection	
• for main current circuit	screw-type terminals
• for auxiliary and control current circuit	screw-type terminals
Identification number and letter for switching elements	21

Mechanical design:		
Mounting type		screw fixing
Mounting type / series installation		Yes
Width	mm	174
Height	mm	200
Depth	mm	282

Certificates/approvals:

General Product Approval







Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

Cax online generator:

http://www.siemens.com/cax

 ${\bf Service \& Support~(Manuals,~Certificates,~Characteristics,~FAQs,...)}$

http://support.automation.siemens.com/WW/view/en/3TB5617-0LJ8/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TB5617-0LJ8}$

last change: Jun 16, 2014