

REVERSING CONTACTOR ASSEMBLY SIZE 00, AC-3, 4 kW/400 V AC OPERATION AC 120V 60HZ/AC 110V 50HZ

General technical data:	
Product function	reversing contactor
Mounting type	screw fixing
Protection class IP on the front	IP00
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	Q
Control circuit/ Control:	
Type of voltage of the control supply voltage	AC
Control supply voltage frequency	1 rated value 50 Hz 2 rated value 60 Hz
Control supply voltage 1	- at AC - at 50 Hz rated value 110 V - at 60 Hz rated value 120 V
Main circuit:	
Operating current at AC-3 at 400 V rated value	9 A
Operating power at AC-3 at 400 V rated value	4 kW
Auxiliary circuit:	
Number of NO contacts for auxiliary contacts per direction of rotation	0
Number of NC contacts for auxiliary contacts per direction of rotation	1
Connections/ Terminals:	
Type of electrical connection for main current circuit	screw-type terminals
Ambient conditions:	
Ambient temperature during operation	-25 ... +55 °C
Certificates/ approvals:	

General Product Approval				Declaration of Conformity	Test Certificates
 CCC	 CSA	 UL		 EG-Konf.	spezielle Prüfbescheinigunge n

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TD2000-1QK6>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TD2000-1QK6>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TD2000-1QK6&lang=en

last modified:

10/07/2016