

REVERSING CONTACTOR ASSEMBLY SIZE 00, AC-3, 4 kW/400 V DC OPERATION DC 24 V

General technical data:	
Product function	reversing contactor
Mounting type	screw fixing
Protection class IP on the front	IP00
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	Q

Control circuit/ Control:	
Type of voltage of the control supply voltage	DC
Control supply voltage 1	24 V
• at DC rated value	

Main circuit:	
Operating current at AC-3 at 400 V rated value	9 A
Operating power at AC-3 at 400 V rated value	4 kW

Auxiliary circuit:	
Number of NO contacts for auxiliary contacts per direction of rotation	2
Number of NC contacts for auxiliary contacts per direction of rotation	2

Connections/ Terminals:	
Type of electrical connection for main current circuit	screw-type terminals

Ambient conditions:	
Ambient temperature during operation	-25 ... +55 °C

Certificates/ approvals:		
--------------------------	--	--

General Product Approval	Declaration of Conformity	Test Certificates
 CCC	 EAC	 EG-Konf.
 CSA		spezielle Prüfbescheinigung n
 UL		

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TD2002-2BB4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TD2002-2BB4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TD2002-2BB4&lang=en

last modified:

10/07/2016