

REVERSING STARTER SIZE 14, AC-3,
335KW/400V AC OPERATION AC 200 TO 240V 50/60HZ

General details:

Product function		reversing contactor
Size of the contactor		14
Mounting type		screw fixing
Protection class IP / on the front		IP00
Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		K
Reference code / according to DIN EN 61346-2		Q
Width	mm	520
Height	mm	310
Depth	mm	278

Control circuit:

Voltage type / of control feed voltage		AC
Control supply voltage frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Control supply voltage / 1		
• at 50 Hz		
• for AC	V	200 ... 240
• at 60 Hz		
• for AC	V	200 ... 240

Main circuit:

Operating current / at AC-3 / at 400 V / rated value	A	630
Service power / at AC-3 / at 400 V / rated value	kW	335

Auxiliary circuit:

Number of NO contacts / for auxiliary contacts / per direction of rotation		4
Number of NC contacts / for auxiliary contacts / per direction of rotation		4

Connection type:

Design of the electrical connection / for main current circuit		screw-type terminals
--	--	----------------------

Ambient conditions:

Ambient temperature

- during operating

°C

55 ... -25

Certificates/approvals:

General Product Approval

other



[Declaration of Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3TD6804-2CM7/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TD6804-2CM7

last change:

Jun 16, 2014