

CONTACTOR SIZE 00 3-POLE AC-3 4KW/400V, SOLDER-PIN
CONNECT., SCREW CONNECTION (DIAGONAL)DC SOLENOID
SYSTEM 24V DC, CUSTOMIZED



Figure similar

General technical data:	
Size of contactor	0
Protection class IP on the front	IP00
Ambient temperature during operation	55 ... -25 °C
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	Q
Main circuit:	
Number of poles for main current circuit	3
Operating current at AC-1 at 400 V • at ambient temperature 40 °C rated value	16 A
Number of NC contacts for main contacts	0
Number of NO contacts for main contacts	3
Operating current at AC-3 at 400 V rated value	9 A
Operating power • at AC-1 at 400 V rated value • at AC-3 at 400 V rated value	10 kW 4 kW

Control circuit/ Control:	
Control version of the switch operating mechanism	conventional
Type of voltage of the control supply voltage	DC
Control supply voltage	24 V
• at DC — rated value	

Auxiliary circuit:	
Number of NC contacts for auxiliary contacts	0
• lagging switching • instantaneous contact	
Number of NO contacts for auxiliary contacts	0
• leading contact • instantaneous contact	

Connections/ Terminals:	
Type of electrical connection	solder pin connectors
• for main current circuit • for auxiliary and control current circuit	
Identification number and letter for switching elements	01 E

Mechanical data:	
Mounting type	screw fixing
Mounting type Side-by-side mounting	Yes
Width	50 mm
Height	36 mm
Depth	63 mm

Certificates/ approvals:

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity
--------------------------	---------------------------------------	---------------------------



CCC



CSA



UR



[Baumusterbescheinigung](#)



EG-Konf.

Test Certificates	Shipping Approval	other
-------------------	-------------------	-------

[spezielle Prüfbescheinigung](#)
[n](#)



DNV



GL



RMRS

[sonstig](#)

[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TF2000-6BB40-0KC0-Z X90>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TF2000-6BB40-0KC0-Z X90>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TF2000-6BB40-0KC0-Z X90&lang=en

last modified:

07/10/2016