



CONT. RELAY 22 E DIN EN 50 011 2NO+2NC,
SCREW CONNECTION ALT. CURRENT ACTUATING 230
V AC 50 HZ,
277 V 60 HZ

General details:		
Size of the contactor		0
Ambient temperature during operating	°C	-25 ... +55
Protection class IP / on the front		IP00
Reference code - according to DIN 40719 extended according to IEC 204-2 / according to IEC 750 - according to DIN EN 61346-2 - according to DIN EN 81346-2		K K K

Control circuit:		
Voltage type / of control feed voltage		AC
Control supply voltage frequency 1 2	Hz Hz	50 60
Control supply voltage - at 50 Hz / at AC / rated value - at 60 Hz / at AC / rated value	V V	230 277

Auxiliary circuit:		
--------------------	--	--

Operating current / at AC-15 • at 230 V / rated value • at 400 V / rated value	A	4
	A	3
Identification number and letter for switching elements		22 E
Number of NC contacts / for auxiliary contacts • lagging switching • delayed switching • asynchronous switching		2
		0
		0
		0
Number of NO contacts / for auxiliary contacts • leading switching • delayed switching • asynchronous switching		2
		0
		0
		0
Number of changeover contacts / for auxiliary contacts		0

Connection type:

Design of the electrical connection / for auxiliary and control current circuit

screw-type terminals

Mechanical design:

Mounting type

screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022

Width

mm

45

Height

mm

48

Depth

mm

64.5

Certificates/approvals:

General Product Approval

**Functional Safety /
Safety of
Machinery**

**Declaration of
Conformity**



CCC



CSA



UL

[Type Examination](#)



EG-Konf.

Test Certificates

Shipping Approval

[other](#)

[Special Test
Certificate](#)

[Type Test
Certificates/Test
Report](#)



LRS



RMRS

other

[Declaration of
Conformity](#)

[other](#)

[Environmental
Confirmations](#)

Safety:

Protection against electrical shock

finger-safe

B10 value / with high demand rate

- according to SN 31920

- note

T1 value / for proof test interval or service life / according to IEC 61508

	400,000
	With 0.3 x Ie
a	20

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3TH2022-4AP0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TH2022-4AP0

last change:

Jun 16, 2014