



CONTACTOR RELAY 31E DIN EN50011 3NO+1NC,
SCREW TERMINALS BRIDGE-CONN.RECTIFIER
INCORPOR. AC OPERATION AC 50/60HZ 230V

General details:		
Size of the contactor		0
Ambient temperature		
• during operating	°C	-25 ... +55
Protection class IP / on the front		IP20
Reference code		
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		K
• according to DIN EN 61346-2		K
• according to DIN EN 81346-2		K

Control circuit:		
Voltage type / of control feed voltage		AC
Control supply voltage frequency		
• 1	Hz	50
• 2	Hz	60
Control supply voltage		
• at 50 Hz / at AC / rated value	V	230
• at 60 Hz / at AC / rated value	V	230

Auxiliary circuit:		
--------------------	--	--

Operating current / at AC-15 • at 230 V / rated value • at 400 V / rated value	A	4
	A	3
Identification number and letter for switching elements		31 E
Number of NC contacts / for auxiliary contacts • lagging switching • delayed switching • asynchronous switching		1
		0
		0
		0
Number of NO contacts / for auxiliary contacts • leading switching • delayed switching • asynchronous switching		3
		0
		0
		0
Number of changeover contacts / for auxiliary contacts		0

Connection type:

Design of the surge suppressor		with full-wave rectification
Design of the electrical connection / for auxiliary and control current circuit		screw-type terminals

Mechanical design:

Mounting type		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Width	mm	45
Height	mm	48
Depth	mm	68

Certificates/approvals:

General Product Approval	Functional Safety / Safety of Machinery	Declaration of Conformity
---------------------------------	--	----------------------------------



CCC



CSA



UL

[Type Examination](#)



EG-Konf.

Test Certificates

[other](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

Shipping Approval



LRS



RMRS

other

[Declaration of Conformity](#)

[Environmental Confirmations](#)

Safety:

Protection against electrical shock		finger-safe
--	--	-------------

B10 value / with high demand rate • according to SN 31920 • note		400,000 With 0.3 x I _e
T1 value / for proof test interval or service life / according to IEC 61508	a	20

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3TH2031-0QL2/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TH2031-0QL2

last change:

Jun 16, 2014