

CONTACTOR RELAY 44E EN 50 011 4N0+4NC,  
SCREW TERMINALS WIDTH 45MM DC OPERATION DC  
SOLENOID SYSTEM DC 230V



| General details:                                                                |    |             |
|---------------------------------------------------------------------------------|----|-------------|
| Size of the contactor                                                           |    | 0           |
| Ambient temperature                                                             |    |             |
| • during operating                                                              | °C | -25 ... +55 |
| Protection class IP / on the front                                              |    | IP20        |
| Reference code                                                                  |    |             |
| • according to DIN 40719 extended according to IEC 204-2 / according to IEC 750 |    | K           |
| • according to DIN EN 61346-2                                                   |    | K           |
| • according to DIN EN 81346-2                                                   |    | K           |
| Control circuit:                                                                |    |             |
| Voltage type / of control feed voltage                                          |    | DC          |
| Control supply voltage                                                          |    |             |
| • for DC / rated value                                                          | V  | 230         |
| Auxiliary circuit:                                                              |    |             |
| Operating current / at AC-15                                                    |    |             |
| • at 230 V / rated value                                                        | A  | 4           |
| • at 400 V / rated value                                                        | A  | 3           |
| Identification number and letter for switching elements                         |    | 44 E        |

|                                                               |  |   |
|---------------------------------------------------------------|--|---|
| <b>Number of NC contacts / for auxiliary contacts</b>         |  | 4 |
| • lagging switching                                           |  | 0 |
| • delayed switching                                           |  | 0 |
| • asynchronous switching                                      |  | 0 |
| <b>Number of NO contacts / for auxiliary contacts</b>         |  | 4 |
| • leading switching                                           |  | 0 |
| • delayed switching                                           |  | 0 |
| • asynchronous switching                                      |  | 0 |
| <b>Number of changeover contacts / for auxiliary contacts</b> |  | 0 |

#### Connection type:

**Design of the electrical connection / for auxiliary and control current circuit**

screw-type terminals

#### Mechanical design:

**Mounting type**

screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022

**Width**

mm 45

**Height**

mm 48

**Depth**

mm 96

#### Certificates/approvals:

**General Product Approval**

**Functional Safety /  
Safety of  
Machinery**

**Declaration of  
Conformity**



CCC



CSA



UL

[Type Examination](#)



EG-Konf.

**Test Certificates**

**Shipping Approval**

[other](#)

[Special Test  
Certificate](#)

[Type Test  
Certificates/Test  
Report](#)



GL



LRS

**other**

[Declaration of  
Conformity](#)

[other](#)

[Environmental  
Confirmations](#)

#### Safety:

**Protection against electrical shock**

finger-safe

**B10 value / with high demand rate**

- according to SN 31920
- note

400,000  
With 0.3 x I<sub>e</sub>

**T1 value / for proof test interval or service life / according to IEC 61508**

a

20

#### Further information:

---

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

---

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

---

**Cax online generator**

<http://www.siemens.com/cax>

---

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3TH2244-0BP4/all>

---

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3TH2244-0BP4](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TH2244-0BP4)

---

last change:

Jun 16, 2014