# **SIEMENS**

Product data sheet 3TH4275-0HP0

CONTACTOR RELAY 53E ACCORDING TO DIN EN 50 011 5NO+3NC,

1 OVERLAPPING CONTACT SCREW TERMINALS WITH SURGE LIMITER (VARISTOR) AC OPERATION AC 230/220V 50HZ, 276/264V 60HZ

General details:		
Size of the contactor		0
Ambient temperature		
during operating	°C	-25 +55
Protection class IP / on the front		IP20
Reference code		
<ul> <li>according to DIN 40719 extended according to IEC 204-2 / according to IEC 750</li> </ul>		К
• according to DIN EN 61346-2		К
according to DIN EN 81346-2		К

Control circuit:		
Voltage type / of control feed voltage		AC
Control supply voltage frequency		
• 1	Hz	50
• 2	Hz	60
Control supply voltage		
• at 50 Hz / at AC / rated value	V	230
• at 60 Hz / at AC / rated value	V	277

Auxiliary circuit:		
Operating current / at AC-15		
• at 230 V / rated value	Α	10
• at 400 V / rated value	Α	6
Identification number and letter for switching elements		53 E, 1U
Number of NC contacts / for auxiliary contacts		2
lagging switching		1
delayed switching		0
asynchronous switching		1
Number of NO contacts / for auxiliary contacts		4
leading switching		1

delayed switching	0
asynchronous switching	1
Number of changeover contacts / for auxiliary contacts	0

Connection type:	
Design of the surge suppressor	with varistor
Design of the electrical connection / for auxiliary and control current circuit	screw-type terminals

Mechanical design:		
Mounting type		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Width	mm	45
Height	mm	78
Depth	mm	102

# Certificates/approvals:

### **General Product Approval**

Functional Safety / Safety of Machinery









Type Examination

#### **Test Certificates**

Shipping Approval

other

Special Test Certificate Type Test
Certificates/Test
Report



## other

Declaration of Conformity

other

Environmental Confirmations

## Safety:

Protection against electrical shock		finger-safe
B10 value / with high demand rate		
according to SN 31920		1,000,000
• note		With 0.3 x le
T1 value / for proof test interval or service life / according to IEC 61508	а	20

# Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

Cax online generator

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3TH4275-0HP0/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3TH4275-0HP0

last change: Jun 16, 2014