



CONT. RELAY 100E DIN EN 50011 8NO+2NC,
SCREW CONNECTION DIR. CURRENT ACTUATING DC
MAGNET SYSTEM INTEGR. VARISTOR 33 V DC

General details:		
Size of the contactor		0
Ambient temperature during operating	°C	-40 ... +70
Protection class IP / on the front		IP20
Reference code - according to DIN 40719 extended according to IEC 204-2 / according to IEC 750 - according to DIN EN 61346-2 - according to DIN EN 81346-2		K K K

Control circuit:		
Voltage type / of control feed voltage		DC
Control supply voltage - for DC / rated value - for DC - rated value	V V	33 24 ... 42

Auxiliary circuit:		
Operating current / at AC-15 at 230 V / rated value	A	10

• at 400 V / rated value	A	6
Identification number and letter for switching elements		82 E
Number of NC contacts / for auxiliary contacts		2
• lagging switching		0
• delayed switching		0
• asynchronous switching		0
Number of NO contacts / for auxiliary contacts		8
• leading switching		0
• delayed switching		0
• asynchronous switching		0
Number of changeover contacts / for auxiliary contacts		0

Connection type:

Design of the surge suppressor		with varistor
Design of the electrical connection / for auxiliary and control current circuit		screw-type terminals

Mechanical design:

Mounting type		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Width	mm	55
Height	mm	78
Depth	mm	135

Certificates/approvals:

General Product Approval



Functional Safety / Safety of Machinery

[Type Examination](#)

Test Certificates

[other](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

Shipping Approval



[other](#)

[Declaration of Conformity](#)

[other](#)

[Environmental Confirmations](#)

Safety:

Protection against electrical shock		finger-safe
B10 value / with high demand rate		1,000,000
• according to SN 31920		With 0.3 x Ie
• note		

T1 value / for proof test interval or service life / according to IEC 61508

a

20

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator



<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3TH4382-0LC8/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TH4382-0LC8



\\W9.4444;
\\W9.25; 3TH439

last change:

Jun 16, 2014