



OPENING DELAY DEVICE AC 110V 50/60HZ, 0.15 OR 0.3S AC 220V 50/60HZ, 0.6 OR 1.2S AC 230V 50/60HZ, 0.6 OR 1.2S

General technical data:		
Product designation		opening delay device for contactor
Design of the product		OFF delay device
Ambient temperature		
• during storage	°C	-40 ... +80
• during operation	°C	-20 ... +60
Product component protective wiring		No
Control circuit/ Control:		
Type of voltage of the control supply voltage		AC
Control supply voltage frequency		
• 1		
— rated value	Hz	60
Control supply voltage 1		
• at AC		
— at 60 Hz rated value	V	220
Installation/ mounting/ dimensions:		
Mounting position		any

Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail
---------------	--

Connections/ Terminals:

Type of electrical connection for auxiliary and control current circuit	screw-type terminals
---	----------------------

Certificates/ approvals:

General Product Approval		Declaration of Conformity	Test Certificates	Shipping Approval
 CSA	 UL	 EAC	 EG-Konf.	Typprüfbescheinigung/Werkszeugnis  PRS

Shipping Approval



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX4701-0AN1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX4701-0AN1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX4701-0AN1&lang=en

last modified:

10/07/2016