

OPENING DELAY DEVICE DC 24V, 0.4S OR 0.8S



Figure similar

General technical data:		
Product designation		opening delay device for contactor
Design of the product		OFF delay device
Ambient temperature		
• during storage	°C	-40 ... +80
• during operation	°C	-20 ... +60
Product component protective wiring		No
Control circuit/ Control:		
Type of voltage of the control supply voltage		DC
Control supply voltage 1		
• at DC		
— rated value	V	24
Installation/ mounting/ dimensions:		
Mounting position		any
Mounting type		screw and snap-on mounting onto 35 mm standard mounting rail

Connections/ Terminals:

Type of electrical connection for auxiliary and control current circuit

screw-type terminals

Certificates/ approvals:

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
	 EG-Konf.	Typprüfbescheinigung/Werkszeugnis	 PRS  RINA

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)
<http://www.siemens.com/industrymall>

Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX4701-0BB4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3TX4701-0BB4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX4701-0BB4&lang=en

last modified:

10/07/2016