

RELAY,
1 NO AS REPLACEMENT FOR 24 V COMPLETE UNIT



General technical details:		
Type of voltage		DC
Control supply voltage		
• for DC / rated value		
• minimum	V	12
• maximum	V	12
Switching behaviour		monostable
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Number of changeover contacts / for auxiliary contacts		1
Operating current / of the auxiliary contacts		
• at DC-13		
• at 24 V	A	1
• at 110 V	A	0.2
• at 230 V	A	0.1
• at AC-15		
• at 230 V	A	3
Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		K
Reference code / according to DIN EN 61346-2		K

Mechanical design:

Design of the electrical connection / jumper socket

No

Design of the relay operating mechanism

poled

Design of the switching function

changeover switch

- guided

No

Product component / jumper socket

No

Ambient conditions:

Protection class IP

IP00

Ambient temperature

- during operating

°C

-25 ... +55

Certificates/approvals:

General Product Approval

other



[Declaration of
Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3TX7014-7BQ00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TX7014-7BQ00

last change:

Jun 16, 2014