



OUTPUT COUPLER WITH PLUGGABLE RELAY,
1 CHANGEOVER CONTACT SPRING-LOADED TERMINAL
24 V AC/DC CASING WIDTH 6.2 MM

General technical details:		
Type of voltage		AC/DC
Supply voltage frequency / for auxiliary and control current circuit / rated value		
• minimum	Hz	50
• maximum	Hz	60
Control supply voltage		
• at 50 Hz / at AC / rated value		
• minimum	V	24
• maximum	V	24
• at 60 Hz / at AC / rated value		
• minimum	V	24
• maximum	V	24
• for DC / rated value		
• minimum	V	24
• maximum	V	24
Switching behaviour		monostable
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Number of changeover contacts / for auxiliary contacts		1
Operating current / of the auxiliary contacts		

- at DC-13
- at 24 V
- at 110 V
- at 230 V
- at AC-15
- at 230 V

A	1
A	0.2
A	0.1
A	3

Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750

K

Reference code / according to DIN EN 61346-2

K

Mechanical design:

Design of the electrical connection

spring-loaded terminals

Design of the electrical connection / jumper socket

Yes

Design of the relay operating mechanism

poled

Design of the switching function

changeover switch

- guided

No

Product component / jumper socket

Yes

Width

mm

6.2

Height

mm

89.5

Depth

mm

92

Ambient conditions:

Protection class IP

IP20

Ambient temperature

- during operating

°C

-25 ... +55

Certificates/approvals:

General Product Approval

Test Certificates

other



CCC



UL

[Special Test Certificate](#)

[Declaration of Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3TX7015-1BB00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TX7015-1BB00

last change:

Jun 16, 2014