

SURGE SUPPRESSOR DIODE COMBINATION
(DIODE AND ZENER DIODE) WITH WIRING SPACER
DC 24 TO 250V SHORT BREAKING TIME
F.MOUNTING TO THE COIL TERMINAL FOR
CONTACTOR RELAYS 3TH



Figure similar

General technical data:		
Product designation		surge suppressor
Design of the surge suppressor		with diode assemblies
Control circuit/ Control:		
Type of voltage of the control supply voltage		DC
Control supply voltage 1		
• at DC		
— Initial rated value	V	24
— Final rated value	V	250
Certificates/ approvals:		

General Product Approval		Declaration of Conformity	other
			
CSA	UR	EG-Konf.	Bestätigungen

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7402-3D>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7402-3D>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7402-3D&lang=en

last modified:

10/07/2016