

SURGE SUPPRESSOR VARISTOR WITH WIRE  
 SPACER AC 48 TO 127V/DC 70 TO 150V  
 F.MOUNTING TO THE COIL TERMINAL FOR  
 CONTACTOR SIZE 0 TO 2



Figure similar

General technical data:		
Product designation		surge suppressor
Design of the surge suppressor		with varistor
Control circuit/ Control:		
Type of voltage of the control supply voltage		AC/DC
Control supply voltage frequency		
<ul style="list-style-type: none"> <li>• 1 rated value</li> </ul>	Hz	50
<ul style="list-style-type: none"> <li>• 2 rated value</li> </ul>	Hz	60
Control supply voltage 1		
<ul style="list-style-type: none"> <li>• at DC                             <ul style="list-style-type: none"> <li>— Initial rated value</li> <li>— Final rated value</li> </ul> </li> <li>• at AC                             <ul style="list-style-type: none"> <li>— at 50 Hz Initial rated value</li> <li>— at 50 Hz Final rated value</li> <li>— at 60 Hz Final rated value</li> </ul> </li> </ul>	V	70
	V	150
	V	48
	V	127
	V	127

— at 60 Hz Initial rated value

V

48

#### Certificates/ approvals:

General Product Approval	Declaration of Conformity	other
 CSA	 UR	  EG-Konf.

[Bestätigungen](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3TX7402-3H>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7402-3H>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=3TX7402-3H&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3TX7402-3H&lang=en)

last modified:

10/07/2016