

SURGE SUPPRESSOR VARISTOR WITH LINE
SPACER AC 400...600V FOR MOUNTING ONTO COIL
TERMINAL FOR CONTACTORS SIZE 0...2



Figure similar

General technical data:		
Product designation		surge suppressor
Design of the surge suppressor		with varistor
Control circuit/ Control:		
Type of voltage of the control supply voltage		AC
Control supply voltage frequency		
• 1 rated value	Hz	50
• 2 rated value	Hz	60
Control supply voltage 1		
• at AC		
— at 50 Hz Initial rated value	V	400
— at 50 Hz Final rated value	V	600
— at 60 Hz Final rated value	V	600
— at 60 Hz Initial rated value	V	400
Certificates/ approvals:		

General Product Approval		Declaration of Conformity	other
			
CSA	UR	EG-Konf.	Bestätigungen

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7402-3L>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7402-3L>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7402-3L&lang=en

last modified:

10/07/2016