## **SIEMENS**

Product data sheet 3TY6501-1K

# SECOND.AUXIL.CONTACT BLOCK LEFT, FOR 3TB46 TO 3TB50

| General technical data:                         |    |                                     |  |
|---|----|-------------------------------------|--|
| Acceptability for application                   |    | Contactor relay and power contactor |  |
| Protection class IP / on the front              |    | IP20                                |  |
| Ambient temperature                             |    |                                     |  |
| during storage                                  | °C | -55 +80                             |  |
| during operating                                | °C | -25 +55                             |  |
| Mechanical operating cycles as operating time   |    |                                     |  |
| • typical                                       |    | 10,000,000                          |  |
| Insulation voltage / with degree of pollution 3 |    |                                     |  |
| rated value                                     | V  | 690                                 |  |
| Impulse voltage resistance                      |    |                                     |  |
| • rated value                                   | kV | 6                                   |  |
|   |    |                                     |  |

| Auxiliary circuit:                                       |   |     |
|--|---|-----|
| Number of NC contacts / for auxiliary contacts           |   |     |
| • instantaneous switching                                |   | 1   |
| • lagging switching                                      |   | 0   |
| Number of NO contacts / for auxiliary contacts           |   |     |
| • instantaneous switching                                |   | 1   |
| leading switching  |   | 0   |
| Operating current / of the auxiliary contacts / at AC-12 |   |     |
| • at 24 V  | Α | 10  |
| • at 230 V   | Α | 10  |
| • maximum  | Α | 10  |
| Operating current  |   |     |
| of the auxiliary contacts                                |   |     |
| • at AC-14   |   |     |
| • at 125 V   | Α | 10  |
| • at AC-15   |   |     |
| • at 24 V  | Α | 10  |
| • at 230 V   | Α | 5.6 |
| • at 400 V   | Α | 3.6 |
| Operating current  |   |     |

| • of the auxiliary contacts / at DC-13 |   |      |
|--|---|------|
| • at 24 V                              | Α | 10   |
| • at 60 V                              | Α | 5    |
| • at 110 V                             | Α | 1.14 |
| • at 220 V                             | Α | 0.48 |

| Installation/ mounting/ dimensions: |       |                  |  |
|-------------------------------------|-------|------------------|--|
| Mounting type s                     |       | snap-on mounting |  |
| Width                               | mm    | 12               |  |
| Height                              | mm 70 |                  |  |
| Depth                               | mm    | 51.5             |  |

| Connections/ terminals:                           |                                     |  |  |
|---|-------------------------------------|--|--|
| Design of the electrical connection               |                                     |  |  |
| for auxiliary and control current circuit         | screw-type terminals                |  |  |
| Type of the connectable conductor cross-section   |                                     |  |  |
| for auxiliary contacts                            |                                     |  |  |
| • finely stranded                                 |                                     |  |  |
| <ul> <li>with conductor end processing</li> </ul> | 2x (0.5 1.0 mm²), 2x (0.75 2.5 mm²) |  |  |
| • for AWG conductors / for auxiliary contacts     | 2x (18 12)                          |  |  |

| 21     | - | 2.4 |   |
|--------|---|-----|---|
| (e. 11 |   | ъ.  | æ |
|        |   |     |   |

Product function / positively driven operation to IEC 60947-5-1

Yes

### **Certificates/ approvals:**

#### **General Product Approval**









Declaration of Conformity

other

### Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

Cax online generator

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3TY6501-1K/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3TY6501-1K}}$ 

last change: Jun 16, 2014