

SIMOCODE DP basic unit PROFIBUS DP interface 1.5 Mbaud, RS485 4I/4O freely parameterizable US: 115 V AC, 50/60 Hz 25...100 A, overall width 70 mm Input for thermistor connection Bistable outputs



Figure similar

General technical data	
<b>Product component</b>	
<ul style="list-style-type: none"> <li>input for thermistor connection</li> </ul>	Yes
<b>Protection class IP</b>	IP20
<b>Switching behavior</b>	bistable
Inputs/ Outputs	
<b>Number of inputs</b>	4
<b>Number of outputs</b>	4
Installation/ mounting/ dimensions	
<b>Mounting type</b>	screw and snap-on mounting
<b>Height</b>	85 mm
<b>Width</b>	70 mm
<b>Depth</b>	132.5 mm
Connections/Terminals	
<b>Type of electrical connection</b>	
<ul style="list-style-type: none"> <li>for main current circuit</li> </ul>	straight-through transformers

- for auxiliary and control current circuit

screw-type terminals

### Ambient conditions

#### Ambient temperature

- during operation

-25 ... +60 °C

### Main circuit

#### Number of poles for main current circuit

3

#### Adjustable pick-up value current of the current-dependent overload release

25 ... 100 A

#### Operating voltage

- rated value

110 ... 690 V

#### Operating frequency rated value

50 ... 60 Hz

### Control circuit/ Control

#### Type of voltage

AC

#### Control supply voltage at AC

- at 50 Hz rated value
- at 60 Hz rated value

115 ... 115 V

115 ... 115 V

#### Supply voltage frequency for auxiliary and control current circuit rated value

50 ... 60 Hz

### Auxiliary circuit

#### Number of NO contacts

- for auxiliary contacts

4

### Certificates/approvals

#### General Product Approval



CCC



UL



C-Tick

#### For use in hazardous locations

[Explosion Protection Certificate](#)



ATEX

#### Test

#### Certificates

[Special Test Certificate](#)

#### other

[Miscellaneous](#)

[Confirmation](#)

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF5021-3AJ10-1>

#### Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF5021-3AJ10-1>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**


<https://support.industry.siemens.com/cs/ww/en/ps/3UF5021-3AJ10-1>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3UF5021-3AJ10-1&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF5021-3AJ10-1&lang=en)



last modified:



01/30/2018