

Memory module for the parameterization of SIMOCODE pro S/V  
without PC/PG, Color: titanium gray



Figure similar

## General technical data:

### Ambient temperature

- |                    |                |
|--------------------|----------------|
| • during storage   | -40 ... +80 °C |
| • during operation | -25 ... +60 °C |
| • during transport | -40 ... +80 °C |

## Certificates/ approvals:

| General Product Approval                                                                 | EMC                                                                               | Declaration of Conformity                                                                   | Test Certificates                                                                             |                                                                                                |
|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| <br>CSA |  | <br>C-Tick | <br>EG-Konf. | <a href="#">Special Test Certificate</a><br><a href="#">Type Test Certificates/Test Report</a> |

| Shipping Approval                                                                        | other                                                                                   |                                                                                           |                                                                         |                                                                                                 |
|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <br>ABS | <br>GL | <br>RMRS | <a href="#">Confirmation</a><br><a href="#">PROFIsafe-Certification</a> | <br>Profibus |

| other                                  |
|----------------------------------------|
| <a href="#">PROFINET-Certification</a> |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7901-0AA01-0>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7901-0AA01-0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF7901-0AA01-0>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3UF7901-0AA01-0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7901-0AA01-0&lang=en)



Figure similar



Figure similar