

ADDRESSING PLUG,
FOR ASSIGNING THE PROFIBUS ADDRESS TO A BASIC
UNIT W/O PC/PG TO SIMOCODE PRO W/O PC/PG



General technical data:

product brand name		SIRIUS
product designation		addressing plug
Ambient temperature		
• during storage	°C	-40 ... +80
• during operating	°C	-25 ... +60
• during transport	°C	-40 ... +80
Relative humidity		
• during operating phase	%	5 ... 95

Certificates/approvals:

General Product Approval				EMC	For use in hazardous locations
 CCC	 CSA	 GOST	 UL	 C-TICK	Explosion Protection Certificate
Test Certificates		Shipping Approval			
Special Test Certificate		 ABS	 DNV	 GL	
other					
Confirmation	Declaration of Conformity	 Profibus	PROFINET-Certification	PROFISafe-Certification	other
Further information:					
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs					
Industry Mall (Online ordering system) http://www.siemens.com/industrial-controls/mall					
Cax online generator: http://www.siemens.com/cax					
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/3UF7910-0AA00-0/all					
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3UF7910-0AA00-0					

last change:

Feb 13, 2013