



CONNECTION CABLE;
LENGTH 0,5M;
ROUND;
CONNECTION OF BASIC UNIT TO CURRENT
MEASURING MODULE,
CURRENT/VOLTAGE MEASUR. MODULE,
OPERATOR PANEL OR TO EXPANSION MODULES VIA
SYSTEM INTERFACE

General technical data:		
product brand name		SIRIUS
product designation		connecting cable
Ambient temperature		
• during storage	°C	-40 ... +80
• during operating	°C	-25 ... +60
• during transport	°C	-40 ... +80
Relative humidity		
• during operating phase	%	5 ... 95

Certificates/approvals:

General Product Approval	EMC	For use in hazardous locations	Test Certificates
--------------------------	-----	--------------------------------	-------------------



CCC



GOST



C-TICK

[Explosion Protection Certificate](#)

[Special Test Certificate](#)

Shipping Approval



ABS



BUREAU
VERITAS



DNV



GL



LRS



PRS

other

[Confirmation](#)

[Declaration of Conformity](#)



Profibus

[PROFINET-Certification](#)

[PROFISafe-Certification](#)

[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:


<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3UF7932-0BA00-0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3UF7932-0BA00-0



last change:

Feb 13, 2013