

Bus connection terminal for connection of a PROFIBUS cable to
SIMOCODE pro S



General technical data:	
Product brand name	SIRIUS
Product designation	Bus connection terminal
Design of the product	For shield support and strain relief of the PROFIBUS cable on a SIMOCODE pro S
Ambient temperature	
• during storage	-40 ... +80 °C
• during operation	-25 ... +60 °C
• during transport	-40 ... +80 °C
Certificates/ approvals:	

General Product Approval	EMC	Test Certificates		Shipping Approval
 CSA		 C-Tick	Special Test Certificate Type Test Certificates/Test Report	 ABS

Shipping Approval	other			
 GL	 RMRS	Confirmation	PROFIsafe-Certification	PROFINET-Certification
			 Profibus	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7960-0AA00-0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7960-0AA00-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF7960-0AA00-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7960-0AA00-0&lang=en





