


Power strips can handle up to 210 A for 3TF53/54, 3TD54, 3TE54, 3UA66
Consisting of 3 power strips

Substance Prohibittance (Date)	01.07.2006
Certificates/ approvals	
other	

[Confirmation](#)

Further information

- Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UX1210>
- Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UX1210>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3UX1210>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UX1210&lang=en



Strombänder									Mindest Lochabstand Anschlussschiene Schütz zu Anschlussschiene Überlastrelais	Klemmen- abdeckungen 3TX6 5, 3TX7 4 und 3TX7 5 siehe Teil 3.
Typ	Maß	a	b	c	d	d ₁	e	e ₁		
3UX1 210	165	18	10	12,5	23	28	9	11	49	
3UX1 211	185	25	12,5	12,5	28	28	11	11	40 bis 60	
3UX1 216	290	25	12,5	12,5	28	28	11	11	100	
3UX1 221	185	18	10	10	23	23	9	9	69	

last modified: 12/23/2020