

Power strips can handle up to 400 A for 3TB54-56, 3TF54-57, 3TD54-56 3TE54-56, 3UA/3UC66, 3UA68 Consisting of 3 power strips

Certificates/approvals

other

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UX1211>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UX1211>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UX1211>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UX1211&lang=en



Strombinder									Mindest Lochabstand Anschlussschiene Schütz zu Anschlussschiene Überlastrelais	Klemmen- abdeckungen 3TX6 5, 3TX7 4 und 3TX7 5 siehe Teil 3.
Typ	Maß									
	a	b	c	c ₁	d	d ₁	e	e ₁		
3UX1 210	165	18	10	12,5	23	28	9	11	49	
3UX1 211	185	25	12,5	12,5	28	28	11	11	40 bis 50	
3UX1 216	290	25	12,5	12,5	28	28	11	11	100	
3UX1 221	185	18	10	10	23	23	9	9	69	

last modified:

05/16/2018