



CIRCUIT BREAKER 3VA1 IEC FRAME 100 BREAKING CAPACITY  
CLASS S ICU=36KA @ 415 V 3-POLE, LINE PROTECTION  
TM210, FTFM, IN=100A OVERLOAD PROTECTION IR=100A  
FIXED SHORT CIRCUIT PROTECTION II=10 X IN CABLE  
CONNECTION SHUNT TRIP (STL) 12-30 V DC, 24 V AC 50/60 HZ

| Model                                                                                            |                             |
|--------------------------------------------------------------------------------------------------|-----------------------------|
| product brandname                                                                                | SETRON                      |
| Product designation                                                                              | Molded case circuit breaker |
| Design of the product                                                                            | Line protection             |
| Design of the overcurrent release                                                                | TM210                       |
| Protective function of the overcurrent release                                                   | LI                          |
| Number of poles                                                                                  | 3                           |
| Design of the auxiliary release                                                                  | Shunt trip (STL)            |
| Design of the auxiliary switch                                                                   | Without                     |
| General technical data                                                                           |                             |
| Tension assignée d'isolement Ui                                                                  | 800 V                       |
| Max. rated operational voltage Ue with AC 50/60Hz                                                | 690 V                       |
| Max. rated operational voltage Ue with DC                                                        | 500 V                       |
| Operating power / at AC-3 / at 400 V                                                             | 0 W                         |
| Operating power / at AC-3 / at 230 V                                                             | 0 W                         |
| Active power loss / for rated value of the current / at AC / in hot operating state / per device | 25 W                        |
| Mechanical service life (switching cycles) / typical                                             | 15 000                      |

|                                                                           |         |
|---------------------------------------------------------------------------|---------|
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz | 8 000   |
| Neutral conductors / upgradeable/retrofitable                             | No      |
| Ground fault monitoring version                                           | Without |
| Product function                                                          |         |
| • communication function                                                  | No      |
| • Phase failure detection                                                 | No      |
| • other measurement function                                              | No      |
| Net weight                                                                | 0.9 kg  |

## Electricity

|                                                                   |       |
|-------------------------------------------------------------------|-------|
| Max. rated operational voltage of the size of the circuit-breaker | 100 A |
| Courant permanent assigné Iu                                      | 100 A |
| Operating current                                                 |       |
| • at 40 °C                                                        | 100 A |
| • at 45 °C                                                        | 100 A |
| • at 50 °C                                                        | 100 A |
| • at 55 °C                                                        | 96 A  |
| • at 60 °C                                                        | 94 A  |
| • at 65 °C                                                        | 92 A  |
| • at 70 °C                                                        | 90 A  |

## Switching capacity according to IEC 60947

|                                                           |         |
|-----------------------------------------------------------|---------|
| Switching capacity class of the circuit breaker           | S       |
| Maximum short-circuit current breaking capacity (Icu)     |         |
| • at 240 V                                                | 55 kA   |
| • at 415 V                                                | 36 kA   |
| • at 440 V                                                | 25 kA   |
| • at 690 V                                                | 7 kA    |
| Operational short-circuit current breaking capacity (Ics) |         |
| • at 240 V                                                | 55 kA   |
| • at 415 V                                                | 36 kA   |
| • at 440 V                                                | 25 kA   |
| • at 690 V                                                | 5 kA    |
| Short-circuit current making capacity (Icm)               |         |
| • at 240 V                                                | 121 kA  |
| • at 415 V                                                | 75.6 kA |
| • at 440 V                                                | 52.5 kA |
| • at 690 V                                                | 11.9 kA |

## Adjustable parameters

|                                                         |     |
|---------------------------------------------------------|-----|
| Adjustable response value current / I <sub>g</sub> min. | 0 A |
|---------------------------------------------------------|-----|

|                                             |     |
|---------------------------------------------|-----|
| Adjustable response value current / lg min. | 0 A |
| Adjustable response value current / lg min. | 0 A |
| Adjustable response value current / lg min. | 0 A |
| Adjustable response value current / li min. | 0 A |
| Adjustable response value current / li max. | 0 A |

### Mechanical Design

|        |         |
|--------|---------|
| Height | 130 mm  |
| Width  | 76.2 mm |
| Depth  | 70 mm   |

### Connections

|                                                                                 |                    |
|---------------------------------------------------------------------------------|--------------------|
| Arrangement of electrical connectors / for main current circuit                 | Front terminal     |
| Type of electrical connection / for main current circuit                        | box terminal       |
| Type of connectable conductor cross-section, round conductor terminal, stranded | 1 x (1.5 - 70 mm²) |

### Auxiliary circuit

|                                             |     |
|---------------------------------------------|-----|
| Product component                           |     |
| • undervoltage release                      | No  |
| • Voltage trigger                           | Yes |
| • undervoltage release with leading contact | No  |
| • Trip indicator                            | No  |

### Accessories

|                                            |                                    |
|--------------------------------------------|------------------------------------|
| Product extension / optional / motor drive | No                                 |
| Manufacturer's article number              |                                    |
| • of the supplied basic switch             | <a href="#">3VA1010-4ED36-0AA0</a> |
| • of the integrated auxiliary trip         | 3VA9688-0BL30                      |

### Environmental conditions

|                                    |        |
|------------------------------------|--------|
| Protection class IP / on the front | IP40   |
| Ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

### Certificates

|                                            |   |
|--------------------------------------------|---|
| Equipment marking / acc. to DIN EN 81346-2 | Q |
|--------------------------------------------|---|

| General Product Approval                                                                 |                                                                                          |                                                                                          | EMC                     | Declaration of<br>Conformity                                                               |                                                                                                 |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <br>CCC | <br>VDE | <br>EAC | <a href="#">sonstig</a> | <br>RCM | <br>EG-Konf. |

| Test Certificates                                 | Shipping Approval       |                                                                                          |                                                                                                     |                                                                                           |                                                                                            |
|---------------------------------------------------|-------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| <a href="#">Typprüfbescheinigung/Werkszeugnis</a> | <a href="#">sonstig</a> | <br>ABS | <br>BUREAU VERITAS | <br>GL | <br>LRS |

| Shipping Approval                                                                         | other                   |  |  |  |  |
|-------------------------------------------------------------------------------------------|-------------------------|--|--|--|--|
| <br>RMRS | <a href="#">sonstig</a> |  |  |  |  |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA1010-4ED36-0HA0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VA1010-4ED36-0HA0/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA1010-4ED36-0HA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA1010-4ED36-0HA0)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>



last modified:

10/24/2016