

SWITCH DISCONNECTOR 3VA1 IEC FRAME 250 4-POLE SD100, IN=250A WITHOUT OVERLOAD PROTECTION WITHOUT SHORT CIRCUIT PROT. BUSBAR CONNECTION SHUNT TRIP (STL) 110-127 V DC, AC 50/60 HZ



Model	
product brandname	SENTRON
Product designation	Switch disconnecter
Design of the product	in MCCB design
Number of poles	4
Design of the auxiliary release	Undervoltage release (UVR)
Design of the auxiliary switch	2 auxiliary switches HQ
General technical data	
Tension assignée d'isolement Ui	800 V
Max. rated operational voltage Ue with AC 50/60Hz	690 V
Max. rated operational voltage Ue with DC	600 V
Active power loss / for rated value of the current / at AC / in hot operating state / per device	57 W
Mechanical service life (switching cycles) / typical	15 000
Product function • communication function	No
Electricity	
Courant permanent assigné Iu	250 A

Mechanical Design	
Height	158 mm
Width	140 mm
Depth	70 mm

Connections	
Arrangement of electrical connectors / for main current circuit	Front terminal
Type of electrical connection / for main current circuit	busbar connection

Auxiliary circuit	
Product component	
• undervoltage release	Yes
• Voltage trigger	No
• undervoltage release with leading contact	No
• Trip indicator	No
Number of CO contacts / for auxiliary contacts	2

Accessories	
Product extension / optional / motor drive	Yes

Environmental conditions	
Protection class IP / on the front	IP40
Ambient temperature	
• during operation / minimum	-25 °C
• during operation / maximum	70 °C
• during storage / minimum	-40 °C
• during storage / maximum	80 °C

Certificates	
Equipment marking / acc. to DIN EN 81346-2	Q

General Product Approval	EMC	Declaration of Conformity	Test Certificates
 CCC	 VDE	 EAC	 RCM
		 EG-Konf.	sonstig

other
sonstig

Further information

<http://www.siemens.com/lowvoltage/catalogs>


Industry Mall (Online ordering system)
<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA1225-1AA42-0CC0>

<http://support.automation.siemens.com/WW/view/en/3VA1225-1AA42-0CC0/all>

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA1225-1AA42-0CC0

<http://www.siemens.com/cax>

<http://www.siemens.com/specifications>





last modified:

10/26/2016