



CIRCUIT BREAKER 3VA2 IEC FRAME 100 BREAKING CAPACITY CLASS M ICU=55KA @ 415 V 3-POLE, LINE PROTECTION ETU350, LSI, IN=100A OVERLOAD PROTECTION IR=40A ...100A SHORT CIRCUIT PROTECTION ISD=1,5... 10 X IR, II=12 X IN CABLE CONNECTION UNDERVOLTAGE RELEASE (UVR) 208-230 V AC 50/50 HZ 2 AUXILIARY SWITCH HQ 1 TRIP ALARM SWITCH HQ 1 ELECTRICAL ALARM SWITCH HQ

| Model                                          |                                                                           |
|------------------------------------------------|---------------------------------------------------------------------------|
| product brandname                              | SENTRON                                                                   |
| Product designation                            | Molded case circuit breaker                                               |
| Design of the product                          | Line protection                                                           |
| Design of the overcurrent release              | ETU350                                                                    |
| Protective function of the overcurrent release | LSI                                                                       |
| Number of poles                                | 3                                                                         |
| Design of the auxiliary release                | Undervoltage release (UVR)                                                |
| Design of the auxiliary switch                 | 2 auxiliary switches + 1 trip alarm switch + 1 electrical alarm switch HQ |

| General technical data                                                                           |        |
|--------------------------------------------------------------------------------------------------|--------|
| Tension assignée d'isolement Ui                                                                  | 800 V  |
| Max. rated operational voltage Ue with AC 50/60Hz                                                | 690 V  |
| Active power loss / for rated value of the current / at AC / in hot operating state / per device | 16 W   |
| Mechanical service life (switching cycles) / typical                                             | 20 000 |
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz                        | 12 000 |
| Neutral conductors / upgradeable/retrofitable                                                    | No     |

|                                 |         |
|---------------------------------|---------|
| Ground fault monitoring version | Without |
| Product function                |         |
| • communication function        | No      |
| • Phase failure detection       | No      |
| • other measurement function    | No      |
| Net weight                      | 2.67 kg |

#### Electricity

|                                                                   |         |
|-------------------------------------------------------------------|---------|
| Max. rated operational voltage of the size of the circuit-breaker | 100 A   |
| Courant permanent assigné lu                                      | 100 A   |
| Operating current                                                 |         |
| • at 40 °C                                                        | 100 A   |
| • at 45 °C                                                        | 100 A   |
| • at 50 °C                                                        | 100 A   |
| • at 55 °C                                                        | 96.25 A |
| • at 60 °C                                                        | 92.5 A  |
| • at 65 °C                                                        | 88.75 A |
| • at 70 °C                                                        | 85 A    |

#### Switching capacity according to IEC 60947

|                                                           |        |
|-----------------------------------------------------------|--------|
| Switching capacity class of the circuit breaker           | M      |
| Maximum short-circuit current breaking capacity (Icu)     |        |
| • at 240 V                                                | 85 kA  |
| • at 415 V                                                | 55 kA  |
| • at 440 V                                                | 55 kA  |
| • at 500 V                                                | 36 kA  |
| • at 690 V                                                | 2 kA   |
| Operational short-circuit current breaking capacity (Ics) |        |
| • at 240 V                                                | 85 kA  |
| • at 415 V                                                | 55 kA  |
| • at 440 V                                                | 55 kA  |
| • at 500 V                                                | 36 kA  |
| • at 690 V                                                | 2 kA   |
| Short-circuit current making capacity (Icm)               |        |
| • at 240 V                                                | 187 kA |
| • at 415 V                                                | 121 kA |
| • at 440 V                                                | 121 kA |
| • at 500 V                                                | 79 kA  |
| • at 690 V                                                | 3.4 kA |

#### Adjustable parameters

|                                                         |      |
|---------------------------------------------------------|------|
| Adjustable response value current / I <sub>g</sub> min. | 40 A |
|---------------------------------------------------------|------|

|                                                                    |         |
|--------------------------------------------------------------------|---------|
| Adjustable response value current / I <sub>g</sub> min.            | 100 A   |
| Adjustable response value current / I <sub>g</sub> min.            | 0.5     |
| Adjustable response value current / I <sub>g</sub> min.            | 17      |
| Adjustable response value current / I <sub>g</sub> min.            | 150 A   |
| Adjustable response value current / I <sub>g</sub> min.            | 1 000 A |
| Short-term delayed / tripping switchable / I <sub>2t</sub> =ON/OFF | No      |
| Adjustable response value current / I <sub>g</sub> min.            | 0.02 s  |
| Adjustable response value current / I <sub>g</sub> min.            | 0.4 s   |
| Adjustable response value current / I <sub>i</sub> min.            | 1 200 A |
| Adjustable response value current / I <sub>i</sub> max.            | 1 200 A |

### Mechanical Design

|        |        |
|--------|--------|
| Height | 181 mm |
| Width  | 105 mm |
| Depth  | 86 mm  |

### Connections

|                                                                                 |                              |
|---------------------------------------------------------------------------------|------------------------------|
| Arrangement of electrical connectors / for main current circuit                 | Front terminal               |
| Type of electrical connection / for main current circuit                        | Box terminal                 |
| Type of connectable conductor cross-section, round conductor terminal, stranded | 1 x (6-120 mm <sup>2</sup> ) |

### Auxiliary circuit

|                                                |     |
|------------------------------------------------|-----|
| Product component                              |     |
| • undervoltage release                         | Yes |
| • Voltage trigger                              | No  |
| • undervoltage release with leading contact    | No  |
| • Trip indicator                               | Yes |
| Number of CO contacts / for auxiliary contacts | 4   |

### Accessories

|                                                   |                                    |
|---------------------------------------------------|------------------------------------|
| Product extension / optional / motor drive        | Yes                                |
| Manufacturer's article number                     |                                    |
| • of the supplied basic switch                    | <a href="#">3VA2010-5HN36-0AA0</a> |
| • of the integrated auxiliary switch/alarm switch | <a href="#">3VA9988-0AA12</a>      |
| • of the integrated auxiliary switch/alarm switch | <a href="#">3VA9988-0AB12</a>      |
| • of the integrated auxiliary switch/alarm switch | <a href="#">3VA9988-0AB22</a>      |
| • of the integrated auxiliary trip                | <a href="#">3VA9608-0BB25</a>      |

### Environmental conditions

|                                    |        |
|------------------------------------|--------|
| Protection class IP / on the front | IP40   |
| Ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |

- during storage / minimum
- during storage / maximum

-40 °C

80 °C

## Certificates

Equipment marking / acc. to DIN EN 81346-2

Q

### General Product Approval

EMC

Declaration of  
Conformity



[sonstig](#)



### Test Certificates

### Shipping Approval

[Typprüfbescheinigung/Werkszeugnis](#)

[sonstig](#)



### Shipping Approval

other



[sonstig](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA2010-5HN36-0DL0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VA2010-5HN36-0DL0/all>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2010-5HN36-0DL0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2010-5HN36-0DL0)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>



**last modified:**

10/29/2016