

CIRCUIT BREAKER 3VA2 IEC FRAME 160 BREAKING CAPACITY  
CLASS M ICU=55KA @ 415 V 3-POLE, LINE PROTECTION  
ETU320, LI, IN=63A OVERLOAD PROTECTION IR=25,2A ...63A  
SHORT CIRCUIT PROTECTION II=1,5... 12 X IN CABLE  
CONNECTION 2 AUXILIARY SWITCH HQ 1 TRIP ALARM SWITCH  
HQ

| Model                                          |                                               |
|------------------------------------------------|-----------------------------------------------|
| product brandname                              | SENTRON                                       |
| Product designation                            | Molded case circuit breaker                   |
| Design of the product                          | Line protection                               |
| Design of the overcurrent release              | ETU320                                        |
| Protective function of the overcurrent release | LI                                            |
| Number of poles                                | 3                                             |
| Design of the auxiliary release                | Without auxiliary release                     |
| Design of the auxiliary switch                 | 2 auxiliary switches + 1 trip alarm switch HQ |

| General technical data                                                                           |         |
|--------------------------------------------------------------------------------------------------|---------|
| Tension assignée d'isolement Ui                                                                  | 800 V   |
| Max. rated operational voltage Ue with AC 50/60Hz                                                | 690 V   |
| Active power loss / for rated value of the current / at AC / in hot operating state / per device | 4 W     |
| Mechanical service life (switching cycles) / typical                                             | 20 000  |
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz                        | 12 000  |
| Neutral conductors / upgradeable/retrofitable                                                    | No      |
| Ground fault monitoring version                                                                  | Without |
| Product function                                                                                 |         |
| • communication function                                                                         | No      |
| • Phase failure detection                                                                        | No      |
| • other measurement function                                                                     | No      |
| Net weight                                                                                       | 2.52 kg |

| Electricity                                                       |       |
|-------------------------------------------------------------------|-------|
| Max. rated operational voltage of the size of the circuit-breaker | 160 A |
| Courant permanent assigné Iu                                      | 63 A  |
| Operating current                                                 |       |
| • at 40 °C                                                        | 63 A  |
| • at 45 °C                                                        | 63 A  |
| • at 50 °C                                                        | 63 A  |

|            |           |
|------------|-----------|
| • at 55 °C | 60.6375 A |
| • at 60 °C | 58.275 A  |
| • at 65 °C | 55.9125 A |
| • at 70 °C | 53.55 A   |

#### Switching capacity according to IEC 60947

|                                                           |         |
|-----------------------------------------------------------|---------|
| Switching capacity class of the circuit breaker           | M       |
| Maximum short-circuit current breaking capacity (Icu)     |         |
| • at 240 V                                                | 85 kA   |
| • at 415 V                                                | 55 kA   |
| • at 440 V                                                | 55 kA   |
| • at 500 V                                                | 36 kA   |
| • at 690 V                                                | 2.5 kA  |
| Operational short-circuit current breaking capacity (Ics) |         |
| • at 240 V                                                | 85 kA   |
| • at 415 V                                                | 55 kA   |
| • at 440 V                                                | 55 kA   |
| • at 500 V                                                | 36 kA   |
| • at 690 V                                                | 2.5 kA  |
| Short-circuit current making capacity (Icm)               |         |
| • at 240 V                                                | 187 kA  |
| • at 415 V                                                | 121 kA  |
| • at 440 V                                                | 121 kA  |
| • at 500 V                                                | 79 kA   |
| • at 690 V                                                | 4.25 kA |

#### Adjustable parameters

|                                                       |       |
|-------------------------------------------------------|-------|
| Adjustable response value current / Ig min.           | 25 A  |
| Adjustable response value current / Ig min.           | 63 A  |
| Adjustable response value current / Ig min.           | 0.5   |
| Adjustable response value current / Ig min.           | 17    |
| Short-term delayed / tripping switchable / I2t=ON/OFF | No    |
| Adjustable response value current / Ii min.           | 95 A  |
| Adjustable response value current / Ii max.           | 756 A |

#### Mechanical Design

|        |        |
|--------|--------|
| Height | 181 mm |
| Width  | 105 mm |
| Depth  | 86 mm  |

#### Connections

|                                                                 |                |
|-----------------------------------------------------------------|----------------|
| Arrangement of electrical connectors / for main current circuit | Front terminal |
|-----------------------------------------------------------------|----------------|

|                                                                                 |                                    |
|---------------------------------------------------------------------------------|------------------------------------|
| Type of electrical connection / for main current circuit                        | Box terminal                       |
| Type of connectable conductor cross-section, round conductor terminal, stranded | 1 x (6-120 mm²)                    |
| <b>Auxiliary circuit</b>                                                        |                                    |
| Product component                                                               |                                    |
| • undervoltage release                                                          | No                                 |
| • Voltage trigger                                                               | No                                 |
| • undervoltage release with leading contact                                     | No                                 |
| • Trip indicator                                                                | Yes                                |
| Number of CO contacts / for auxiliary contacts                                  | 3                                  |
| <b>Accessories</b>                                                              |                                    |
| Product extension / optional / motor drive                                      | Yes                                |
| Manufacturer's article number                                                   |                                    |
| • of the supplied basic switch                                                  | <a href="#">3VA2163-5HL36-0AA0</a> |
| • of the integrated auxiliary switch/alarm switch                               | <a href="#">3VA9988-0AA12</a>      |
| • of the integrated auxiliary switch/alarm switch                               | <a href="#">3VA9988-0AB12</a>      |
| <b>Environmental conditions</b>                                                 |                                    |
| Protection class IP / on the front                                              | IP40                               |
| Ambient temperature                                                             |                                    |
| • during operation / minimum                                                    | -25 °C                             |
| • during operation / maximum                                                    | 70 °C                              |
| • during storage / minimum                                                      | -40 °C                             |
| • during storage / maximum                                                      | 80 °C                              |
| <b>Certificates</b>                                                             |                                    |
| Equipment marking / acc. to DIN EN 81346-2                                      | Q                                  |

| General Product Approval                                                                 |                                                                                          |                                                                                          | EMC                     | Declaration of<br>Conformity                                                               |                                                                                                 |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <br>CCC | <br>VDE | <br>EAC | <a href="#">sonstig</a> | <br>RCM | <br>EG-Konf. |

| Test Certificates                                 | Shipping Approval       |                                                                                          |                                                                                                     |                                                                                           |                                                                                            |
|---------------------------------------------------|-------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| <a href="#">Typprüfbescheinigung/Werkszeugnis</a> | <a href="#">sonstig</a> | <br>ABS | <br>BUREAU VERITAS | <br>GL | <br>LRS |

| Shipping Approval                                                                         | other                   |  |  |  |  |
|-------------------------------------------------------------------------------------------|-------------------------|--|--|--|--|
| <br>RMRS | <a href="#">sonstig</a> |  |  |  |  |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA2163-5HL36-0AH0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VA2163-5HL36-0AH0/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2163-5HL36-0AH0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2163-5HL36-0AH0)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>

last modified:

10/29/2016