



CIRCUIT BREAKER 3VA2 IEC FRAME 160 BREAKING CAPACITY CLASS M ICU=55KA @ 415 V 3-POLE, LINE PROTECTION ETU850, LSI, IN=63A OVERLOAD PROTECTION IR=25,2A ...63A SHORT CIRCUIT PROTECTION ISD=0,6..10X IN, II=1,5..12X IN NEUTRAL PROTECTION OPTIONAL WITH EXT. CT BUSBAR CONNECTION 4 AUXILIARY SWITCH HQ

| Model                                                                                            |                             |
|--------------------------------------------------------------------------------------------------|-----------------------------|
| product brandname                                                                                | SENTRON                     |
| Product designation                                                                              | Molded case circuit breaker |
| Design of the product                                                                            | Line protection             |
| Design of the overcurrent release                                                                | ETU850                      |
| Protective function of the overcurrent release                                                   | LSI                         |
| Number of poles                                                                                  | 3                           |
| Design of the auxiliary release                                                                  | Without auxiliary release   |
| Design of the auxiliary switch                                                                   | 4 auxiliary switches HQ     |
| General technical data                                                                           |                             |
| Tension assignée d'isolement Ui                                                                  | 800 V                       |
| Max. rated operational voltage Ue with AC 50/60Hz                                                | 690 V                       |
| Active power loss / for rated value of the current / at AC / in hot operating state / per device | 4 W                         |
| Mechanical service life (switching cycles) / typical                                             | 20 000                      |
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz                        | 12 000                      |
| Neutral conductors / upgradeable/retrofitable                                                    | Yes                         |
| Ground fault monitoring version                                                                  | Without                     |

|                              |         |
|------------------------------|---------|
| Product function             |         |
| • communication function     | Yes     |
| • Phase failure detection    | No      |
| • other measurement function | Yes     |
| Net weight                   | 2.42 kg |

#### Electricity

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| Max. rated operational voltage of the size of the circuit-breaker | 160 A     |
| Courant permanent assigné Iu                                      | 63 A      |
| Operating current                                                 |           |
| • at 40 °C                                                        | 63 A      |
| • at 45 °C                                                        | 63 A      |
| • at 50 °C                                                        | 63 A      |
| • at 55 °C                                                        | 60.6375 A |
| • at 60 °C                                                        | 58.275 A  |
| • at 65 °C                                                        | 55.9125 A |
| • at 70 °C                                                        | 53.55 A   |

#### Switching capacity according to IEC 60947

|                                                           |         |
|-----------------------------------------------------------|---------|
| Switching capacity class of the circuit breaker           | M       |
| Maximum short-circuit current breaking capacity (Icu)     |         |
| • at 240 V                                                | 85 kA   |
| • at 415 V                                                | 55 kA   |
| • at 440 V                                                | 55 kA   |
| • at 500 V                                                | 36 kA   |
| • at 690 V                                                | 2.5 kA  |
| Operational short-circuit current breaking capacity (Ics) |         |
| • at 240 V                                                | 85 kA   |
| • at 415 V                                                | 55 kA   |
| • at 440 V                                                | 55 kA   |
| • at 500 V                                                | 36 kA   |
| • at 690 V                                                | 2.5 kA  |
| Short-circuit current making capacity (Icm)               |         |
| • at 240 V                                                | 187 kA  |
| • at 415 V                                                | 121 kA  |
| • at 440 V                                                | 121 kA  |
| • at 500 V                                                | 79 kA   |
| • at 690 V                                                | 4.25 kA |

#### Adjustable parameters

|                                                         |      |
|---------------------------------------------------------|------|
| Adjustable response value current / I <sub>g</sub> min. | 25 A |
| Adjustable response value current / I <sub>g</sub> min. | 63 A |

|                                                                    |        |
|--------------------------------------------------------------------|--------|
| Adjustable response value current / I <sub>g</sub> min.            | 0.5    |
| Adjustable response value current / I <sub>g</sub> min.            | 25     |
| Adjustable response value current / I <sub>g</sub> min.            | 38 A   |
| Adjustable response value current / I <sub>g</sub> min.            | 630 A  |
| Short-term delayed / tripping switchable / I <sub>2t</sub> =ON/OFF | Yes    |
| Adjustable response value current / I <sub>g</sub> min.            | 0.05 s |
| Adjustable response value current / I <sub>g</sub> min.            | 0.5 s  |
| Adjustable response value current / I <sub>g</sub> min.            | 0.05 s |
| Adjustable response value current / I <sub>g</sub> min.            | 0.5 s  |
| Adjustable response value current / I <sub>i</sub> min.            | 95 A   |
| Adjustable response value current / I <sub>i</sub> max.            | 756 A  |

### Mechanical Design

|        |        |
|--------|--------|
| Height | 181 mm |
| Width  | 105 mm |
| Depth  | 86 mm  |

### Connections

|                                                                                         |                |
|-----------------------------------------------------------------------------------------|----------------|
| Arrangement of electrical connectors / for main current circuit                         | Front terminal |
| Type of electrical connection / for main current circuit                                | Lug terminal   |
| Type of connectable conductor cross-section, connection screw, width x thickness , min. | 13 x 1 mm      |
| Type of connectable conductor cross-section, connection screw, width x thickness , max. | 25 x 8.5       |

### Auxiliary circuit

|                                                |    |
|------------------------------------------------|----|
| Product component                              |    |
| • undervoltage release                         | No |
| • Voltage trigger                              | No |
| • undervoltage release with leading contact    | No |
| • Trip indicator                               | No |
| Number of CO contacts / for auxiliary contacts | 4  |

### Accessories

|                                                   |                                    |
|---------------------------------------------------|------------------------------------|
| Product extension / optional / motor drive        | Yes                                |
| Manufacturer's article number                     |                                    |
| • of the supplied basic switch                    | <a href="#">3VA2163-5KP32-0AA0</a> |
| • of the integrated auxiliary switch/alarm switch | <a href="#">3VA9988-0AA12</a>      |

### Environmental conditions

|                                    |        |
|------------------------------------|--------|
| Protection class IP / on the front | IP40   |
| Ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |

- during storage / minimum
- during storage / maximum

-40 °C

80 °C

## Certificates

Equipment marking / acc. to DIN EN 81346-2

Q

### General Product Approval

### EMC

### Declaration of Conformity

### Test Certificates



[sonstig](#)



EG-Konf.

[Typprüfbescheinigung/Werkszeugnis](#)

### Test Certificates

### Shipping Approval

[sonstig](#)



GL



LRS



RMRS

### other

[sonstig](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA2163-5KP32-0AE0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VA2163-5KP32-0AE0/all>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2163-5KP32-0AE0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2163-5KP32-0AE0)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>



**last modified:**

10/29/2016