



CIRCUIT BREAKER 3VA2 IEC FRAME 250 BREAKING CAPACITY CLASS M ICU=55KA @ 415 V 3-POLE, LINE PROTECTION ETU560, LSIG, IN=250A OVERLOAD PROTECTION IR=100A ...250A SHORT CIRCUIT PROTECTION ISD=0,6..10X IN, II=1,5..10X IN NEUTRAL PROTECTION OPTIONAL WITH EXT. CT GROUND-FAULT, SWITCHABLE IG=0,2... 1 X IN, TG=0,05-0,8S BUSBAR CONNECTION SHUNT TRIP (STL) 110-127 V DC; AC 50/60 HZ

| Model                                                                                            |                                         |
|--------------------------------------------------------------------------------------------------|-----------------------------------------|
| product brandname                                                                                | SENTRON                                 |
| Product designation                                                                              | Molded case circuit breaker             |
| Design of the product                                                                            | Line protection                         |
| Design of the overcurrent release                                                                | ETU560                                  |
| Protective function of the overcurrent release                                                   | LSIG                                    |
| Number of poles                                                                                  | 3                                       |
| Design of the auxiliary release                                                                  | Shunt trip (STL)                        |
| Design of the auxiliary switch                                                                   | Without                                 |
| General technical data                                                                           |                                         |
| Tension assignée d'isolement Ui                                                                  | 800 V                                   |
| Max. rated operational voltage Ue with AC 50/60Hz                                                | 690 V                                   |
| Active power loss / for rated value of the current / at AC / in hot operating state / per device | 48 W                                    |
| Mechanical service life (switching cycles) / typical                                             | 20 000                                  |
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz                        | 10 000                                  |
| Neutral conductors / upgradeable/retrofitable                                                    | Yes                                     |
| Ground fault monitoring version                                                                  | Summation current formation L-conductor |

|                              |         |
|------------------------------|---------|
| Product function             |         |
| • communication function     | Yes     |
| • Phase failure detection    | No      |
| • other measurement function | No      |
| Net weight                   | 2.49 kg |

#### Electricity

|                                                                   |       |
|-------------------------------------------------------------------|-------|
| Max. rated operational voltage of the size of the circuit-breaker | 250 A |
| Courant permanent assigné Iu                                      | 250 A |
| Operating current                                                 |       |
| • at 40 °C                                                        | 250 A |
| • at 45 °C                                                        | 250 A |
| • at 50 °C                                                        | 250 A |
| • at 55 °C                                                        | 238 A |
| • at 60 °C                                                        | 225 A |
| • at 65 °C                                                        | 213 A |
| • at 70 °C                                                        | 200 A |

#### Switching capacity according to IEC 60947

|                                                           |        |
|-----------------------------------------------------------|--------|
| Switching capacity class of the circuit breaker           | M      |
| Maximum short-circuit current breaking capacity (Icu)     |        |
| • at 240 V                                                | 85 kA  |
| • at 415 V                                                | 55 kA  |
| • at 440 V                                                | 55 kA  |
| • at 500 V                                                | 36 kA  |
| • at 690 V                                                | 3 kA   |
| Operational short-circuit current breaking capacity (Ics) |        |
| • at 240 V                                                | 85 kA  |
| • at 415 V                                                | 55 kA  |
| • at 440 V                                                | 55 kA  |
| • at 500 V                                                | 36 kA  |
| • at 690 V                                                | 3 kA   |
| Short-circuit current making capacity (Icm)               |        |
| • at 240 V                                                | 187 kA |
| • at 415 V                                                | 121 kA |
| • at 440 V                                                | 121 kA |
| • at 500 V                                                | 79 kA  |
| • at 690 V                                                | 5.1 kA |

#### Adjustable parameters

|                                                         |       |
|---------------------------------------------------------|-------|
| Adjustable response value current / I <sub>g</sub> min. | 100 A |
| Adjustable response value current / I <sub>g</sub> min. | 250 A |

|                                                                                     |         |
|-------------------------------------------------------------------------------------|---------|
| Adjustable response value current / Ig min.                                         | 0.5     |
| Adjustable response value current / Ig min.                                         | 15      |
| Adjustable response value current / Ig min.                                         | 150 A   |
| Adjustable response value current / Ig min.                                         | 2 500 A |
| Short-term delayed / tripping switchable / I2t=ON/OFF                               | Yes     |
| Adjustable response value current / Ig min.                                         | 0.05 s  |
| Adjustable response value current / Ig min.                                         | 0.5 s   |
| Adjustable response value current / Ig min.                                         | 0.05 s  |
| Adjustable response value current / Ig min.                                         | 0.5 s   |
| Adjustable response value current / li min.                                         | 375 A   |
| Adjustable response value current / li max.                                         | 2 500 A |
| Ground fault protection can be switched ON/OFF                                      | Yes     |
| Adjustable response value current / Ig min.                                         | 50 A    |
| Adjustable response value current / Ig max.                                         | 250 A   |
| Adjustable response value current / for G-tripping / with I2t characteristic / min. | 0.2 A   |
| Adjustable response value current / for G-tripping / with I2t characteristic / max. | 1 A     |

#### Mechanical Design

|        |        |
|--------|--------|
| Height | 181 mm |
| Width  | 105 mm |
| Depth  | 86 mm  |

#### Connections

|                                                                                         |                |
|-----------------------------------------------------------------------------------------|----------------|
| Arrangement of electrical connectors / for main current circuit                         | Front terminal |
| Type of electrical connection / for main current circuit                                | Lug terminal   |
| Type of connectable conductor cross-section, connection screw, width x thickness , min. | 13 x 1 mm      |
| Type of connectable conductor cross-section, connection screw, width x thickness , max. | 25 x 8.5       |

#### Auxiliary circuit

|                                                |     |
|------------------------------------------------|-----|
| Product component                              |     |
| • undervoltage release                         | No  |
| • Voltage trigger                              | Yes |
| • undervoltage release with leading contact    | No  |
| • Trip indicator                               | No  |
| Number of CO contacts / for auxiliary contacts | 0   |

#### Accessories

|                                            |                                    |
|--------------------------------------------|------------------------------------|
| Product extension / optional / motor drive | Yes                                |
| Manufacturer's article number              |                                    |
| • of the supplied basic switch             | <a href="#">3VA2225-5JQ32-0AA0</a> |

- of the integrated auxiliary trip

3VA9688-0BL32

## Environmental conditions

|                                    |        |
|------------------------------------|--------|
| Protection class IP / on the front | IP40   |
| Ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

## Certificates

|                                            |   |
|--------------------------------------------|---|
| Equipment marking / acc. to DIN EN 81346-2 | Q |
|--------------------------------------------|---|

| General Product Approval                                                                     | EMC                                                                                        | Declaration of Conformity                                                                       |
|----------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <br>CCC     | <br>VDE   | <br>EAC        |
| <br>sonstig | <br>RCM | <br>EG-Konf. |

| Test Certificates                                                            | Shipping Approval                                                                                    |
|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <a href="#">Typprüfbescheinigung/Werkszeugnis</a><br><a href="#">sonstig</a> | <br>ABS            |
|                                                                              | <br>BUREAU VERITAS |
|                                                                              | <br>GL           |
|                                                                              | <br>LRS          |

| Shipping Approval                                                                           | other                   |
|---------------------------------------------------------------------------------------------|-------------------------|
| <br>RMRS | <a href="#">sonstig</a> |

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA2225-5JQ32-0JA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VA2225-5JQ32-0JA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2225-5JQ32-0JA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2225-5JQ32-0JA0)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

10/29/2016