SIEMENS

Show actual product details

## Data sheet 3VA2325-7MN32-0CC0

CIRCUIT BREAKER 3VA2 IEC FRAME 400 BREAKING CAPACITY CLASS C ICU=110KA @ 415 V 3-POLE, MOTOR PROTECTION ETU350M, LSI, IN=250A OVERLOAD PROTECTION IR=100A ...250A SHORT CIRCUIT PROTECTION ISD=3... 15 X IR, II=15 X IN BUSBAR CONNECTION SHUNT TRIP (STL) 220-250 V DC, 208-277 V AC

| Model | |
|---|---|
| product brandname | SENTRON |
| Product designation | Molded case circuit breaker |
| Design of the product | Motor protection |
| Design of the overcurrent release | ETU350M |
| Protective function of the overcurrent release | LSI |
| Number of poles | 3 |
| Design of the auxiliary release | Undervoltage release (UVR) |
| Design of the auxiliary switch | 2 auxiliary switches HQ |

| General technical data | |
|---|---|
| Tension assignée d'isolement Ui | 800 V |
| Max. rated operational voltage Ue with AC 50/60Hz | 690 V |
| Operating power / at AC-3 / at 400 V | 110 W |
| Active power loss / for rated value of the current / at AC / in hot operating state / per device | 40 W |
| Active power loss / for rated value of the current / at AC / in hot operating state / per pole | 12.5 W |
| Mechanical service life (switching cycles) / typical | 15 000 |


Subject to change without notice
© Copyright Siemens AG

| | |
|---|---|
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz | 6 000 |
| Neutral conductors / upgradeable/retrofittable | No |
| Ground fault monitoring version | Without |
| Product function | |
| • communication function | No |
| • Phase failure detection | Yes |
| • other measurement function | No |
| Net weight | 4.3 kg |

| Electricity | |
|---|---|
| Max. rated operational voltage of the size of the circuit-breaker | 400 A |
| Courant permanent assigné Iu | 250 A |
| Operating current | |
| • at 40 °C | 250 A |
| • at 45 °C | 250 A |
| • at 50 °C | 250 A |
| • at 55 °C | 240 A |
| • at 60 °C | 235 A |
| • at 65 °C | 230 A |
| • at 70 °C | 225 A |

| Switching capacity according to IEC 60947 | |
|---|---|
| Switching capacity class of the circuit breaker | C |
| Maximum short-circuit current breaking capacity (Icu) | |
| • at 240 V | 150 kA |
| • at 415 V | 110 kA |
| • at 440 V | 110 kA |
| • at 500 V | 85 kA |
| • at 690 V | 25 kA |
| Operational short-circuit current breaking capacity (Ics) | |
| • at 240 V | 150 kA |
| • at 415 V | 110 kA |
| • at 440 V | 110 kA |
| • at 500 V | 85 kA |
| • at 690 V | 25 kA |
| Short-circuit current making capacity (Icm) | |
| • at 240 V | 330 kA |
| • at 415 V | 242 kA |
| • at 440 V | 242 kA |
| • at 500 V | 187 kA |
| • at 690 V | 52.5 kA |


Subject to change without notice
© Copyright Siemens AG

| Adjustable parameters | |
|---|---|
| Adjustable response value current / Ig min. | 100 A |
| Adjustable response value current / Ig min. | 250 A |
| Adjustable response value current / Ig min. | 4 |
| Adjustable response value current / Ig min. | 17 |
| Adjustable response value current / Ig min. | 750 A |
| Adjustable response value current / Ig min. | 3 750 A |
| Short-term delayed / tripping switchable / I2t=ON/OFF | No |
| Adjustable response value current / Ig min. | 0.03 s |
| Adjustable response value current / Ig min. | 0.03 s |
| Adjustable response value current / Ii min. | 3 750 A |
| Adjustable response value current / Ii max. | 3 750 A |

| Mechanical Design | |
|---|---|
| Height | 248 mm |
| Width | 138 mm |
| Depth | 110 mm |

| Connections | |
|---|---|
| Arrangement of electrical connectors / for main current circuit | Front terminal |
| Type of electrical connection / for main current circuit | Lug terminal |

| Auxiliary circuit | |
|---|---|
| Product component | |
| • undervoltage release | Yes |
| • Voltage trigger | No |
| • undervoltage release with leading contact | No |
| • Trip indicator | No |
| Number of CO contacts / for auxiliary contacts | 2 |

| Accessories | |
|---|---|
| Product extension / optional / motor drive | Yes |
| Manufacturer's article number | |
| • of the supplied basic switch | 3VA2325-7MN32-0AA0 |
| • of the integrated auxiliary switch/alarm switch | 3VA9988-0AA12 |
| • of the integrated auxiliary trip | 3VA9608-0BB24 |

| Environmental conditions | |
|---|---|
| Protection class IP / on the front | IP40 |
| Ambient temperature | |
| • during operation / minimum | -25 °C |
| • during operation / maximum | 70 °C |
| • during storage / minimum | -40 °C |


Subject to change without notice
© Copyright Siemens AG

| | |
|---|---|
| • during storage / maximum | 80 °C |

## Certificates

| | |
|---|---|
| Equipment marking / acc. to DIN EN 81346-2 | Q |

| General Product Approval | | | EMC | Declaration of Conformity | Test Certificates |
|---|---|---|---|---|---|
| CCC | VDE | | RCM | EG-Konf. | sonstig |

| other | |
|---|---|
| Bestätigungen | sonstig |

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,…)**
http://www.siemens.com/lowvoltage/catalogs

**Industry Mall (Online ordering system)**
https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA2325-7MN32-0CC0

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
http://support.automation.siemens.com/WW/view/en/3VA2325-7MN32-0CC0/all

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2325-7MN32-0CC0

**CAx-Online-Generator**
http://www.siemens.com/cax

**Tender specifications**
http://www.siemens.com/specifications


Subject to change without notice
© Copyright Siemens AG









Subject to change without notice
© Copyright Siemens AG

| | |
|---|---|
| **last modified:** | 10/29/2016 |


Subject to change without notice
© Copyright Siemens AG