



CIRCUIT BREAKER 3VA2 IEC FRAME 400 BREAKING CAPACITY CLASS M ICU=55KA @ 415 V 3-POLE, LINE PROTECTION ETU350, LSI, IN=400A OVERLOAD PROTECTION IR=160A ...400A SHORT CIRCUIT PROTECTION ISD=1,5... 10 X IR, II=10 X IN BUSBAR CONNECTION SHUNT TRIP (STL) 12-30 V DC, 24 V AC 50/60 HZ 2 AUXILIARY SWITCH HQ 1 TRIP ALARM SWITCH HQ 1 ELECTRICAL ALARM SWITCH HQ

| Model                                          |                                                                           |
|------------------------------------------------|---------------------------------------------------------------------------|
| product brandname                              | SENTRON                                                                   |
| Product designation                            | Molded case circuit breaker                                               |
| Design of the product                          | Line protection                                                           |
| Design of the overcurrent release              | ETU350                                                                    |
| Protective function of the overcurrent release | LSI                                                                       |
| Number of poles                                | 3                                                                         |
| Design of the auxiliary release                | Shunt trip (STL)                                                          |
| Design of the auxiliary switch                 | 2 auxiliary switches + 1 trip alarm switch + 1 electrical alarm switch HQ |

| General technical data                                                                           |        |
|--------------------------------------------------------------------------------------------------|--------|
| Tension assignée d'isolement Ui                                                                  | 800 V  |
| Max. rated operational voltage Ue with AC 50/60Hz                                                | 690 V  |
| Active power loss / for rated value of the current / at AC / in hot operating state / per device | 96 W   |
| Active power loss / for rated value of the current / at AC / in hot operating state / per pole   | 32 W   |
| Mechanical service life (switching cycles) / typical                                             | 15 000 |

|                                                                           |         |
|---------------------------------------------------------------------------|---------|
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz | 6 000   |
| Neutral conductors / upgradeable/retrofitable                             | No      |
| Ground fault monitoring version                                           | Without |
| Product function                                                          |         |
| • communication function                                                  | No      |
| • Phase failure detection                                                 | No      |
| • other measurement function                                              | No      |
| Net weight                                                                | 4.4 kg  |

## Electricity

|                                                                   |       |
|-------------------------------------------------------------------|-------|
| Max. rated operational voltage of the size of the circuit-breaker | 400 A |
| Courant permanent assigné Iu                                      | 400 A |
| Operating current                                                 |       |
| • at 40 °C                                                        | 400 A |
| • at 45 °C                                                        | 400 A |
| • at 50 °C                                                        | 400 A |
| • at 55 °C                                                        | 385 A |
| • at 60 °C                                                        | 370 A |
| • at 65 °C                                                        | 355 A |
| • at 70 °C                                                        | 340 A |

## Switching capacity according to IEC 60947

|                                                           |         |
|-----------------------------------------------------------|---------|
| Switching capacity class of the circuit breaker           | M       |
| Maximum short-circuit current breaking capacity (Icu)     |         |
| • at 240 V                                                | 85 kA   |
| • at 415 V                                                | 55 kA   |
| • at 440 V                                                | 55 kA   |
| • at 500 V                                                | 36 kA   |
| • at 690 V                                                | 10 kA   |
| Operational short-circuit current breaking capacity (Ics) |         |
| • at 240 V                                                | 85 kA   |
| • at 415 V                                                | 55 kA   |
| • at 440 V                                                | 55 kA   |
| • at 500 V                                                | 36 kA   |
| • at 690 V                                                | 10 kA   |
| Short-circuit current making capacity (Icm)               |         |
| • at 240 V                                                | 187 kA  |
| • at 415 V                                                | 121 kA  |
| • at 440 V                                                | 121 kA  |
| • at 500 V                                                | 75.6 kA |
| • at 690 V                                                | 17 kA   |

| Adjustable parameters                                              |         |
|--------------------------------------------------------------------|---------|
| Adjustable response value current / I <sub>g</sub> min.            | 160 A   |
| Adjustable response value current / I <sub>g</sub> min.            | 400 A   |
| Adjustable response value current / I <sub>g</sub> min.            | 0.5     |
| Adjustable response value current / I <sub>g</sub> min.            | 17      |
| Adjustable response value current / I <sub>g</sub> min.            | 0 A     |
| Adjustable response value current / I <sub>g</sub> min.            | 0 A     |
| Short-term delayed / tripping switchable / I <sub>2t</sub> =ON/OFF | No      |
| Adjustable response value current / I <sub>i</sub> min.            | 4 000 A |
| Adjustable response value current / I <sub>i</sub> max.            | 4 000 A |

| Mechanical Design |        |
|-------------------|--------|
| Height            | 248 mm |
| Width             | 138 mm |
| Depth             | 110 mm |

| Connections                                                                             |                |
|-----------------------------------------------------------------------------------------|----------------|
| Arrangement of electrical connectors / for main current circuit                         | Front terminal |
| Type of electrical connection / for main current circuit                                | Lug terminal   |
| Type of connectable conductor cross-section, connection screw, width x thickness , min. | 20 x 1         |
| Type of connectable conductor cross-section, connection screw, width x thickness , max. | 35 x 10        |

| Auxiliary circuit                              |     |
|------------------------------------------------|-----|
| Product component                              |     |
| • undervoltage release                         | No  |
| • Voltage trigger                              | Yes |
| • undervoltage release with leading contact    | No  |
| • Trip indicator                               | Yes |
| Number of CO contacts / for auxiliary contacts | 4   |

| Accessories                                       |                                    |
|---------------------------------------------------|------------------------------------|
| Product extension / optional / motor drive        | Yes                                |
| Manufacturer's article number                     |                                    |
| • of the supplied basic switch                    | <a href="#">3VA2340-5HN32-0AA0</a> |
| • of the integrated auxiliary switch/alarm switch | <a href="#">3VA9988-0AA12</a>      |
| • of the integrated auxiliary switch/alarm switch | <a href="#">3VA9988-0AB12</a>      |
| • of the integrated auxiliary switch/alarm switch | <a href="#">3VA9988-0AB22</a>      |
| • of the integrated auxiliary trip                | 3VA9688-0BL30                      |

| Environmental conditions           |      |
|------------------------------------|------|
| Protection class IP / on the front | IP40 |
| Ambient temperature                |      |

- during operation / minimum
- during operation / maximum
- during storage / minimum
- during storage / maximum

-25 °C  
70 °C  
-40 °C  
80 °C

## Certificates

Equipment marking / acc. to DIN EN 81346-2

Q

### General Product Approval

### EMC

### Declaration of Conformity

### Test Certificates



CCC



VDE



RCM



EG-Konf.

[Typprüfbescheinigung/Werkszeugnis](#)

### Test Certificates

### Shipping Approval

[sonstig](#)



ABS



BUREAU  
VERITAS



GL



LRS



RMRS

### other

[sonstig](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA2340-5HN32-0HL0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VA2340-5HN32-0HL0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2340-5HN32-0HL0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2340-5HN32-0HL0)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



**last modified:**

10/29/2016