



CIRCUIT BREAKER 3VA2 IEC FRAME 630 BREAKING CAPACITY CLASS C ICU=110KA @ 415 V 3-POLE, MOTOR PROTECTION ETU860M, LSIG, IN=500A OVERLOAD PROTECTION IR=200A ...500A SHORT CIRCUIT PROTECTION ISD=1,2... 15 X IN, II=15 X IN NEUTRAL PROTECTION OPTIONAL WITH EXT. CT,UPTO 160% GROUND-FAULT, SWITCHABLE IG=0,2... 1 X IN, TG=0,05-0,8MS BUSBAR CONNECTION UNDERVOLTAGE RELEASE 24 V DC 2 AUXILIARY SWITCH 1 TRIP ALARM SWITCH 1 ELECTRICAL ALARM SWITCH

Certificates

General Product Approval		EMC	Declaration of Conformity	Test Certificates
				
CCC	VDE		RCM	EG-Konf.

[sonstig](#)

other

[Bestätigungen](#)

[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)


<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA2450-7MQ32-0BL0>


<http://support.automation.siemens.com/WW/view/en/3VA2450-7MQ32-0BL0/all>

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2450-7MQ32-0BL0

<http://www.siemens.com/cax>

<http://www.siemens.com/specifications>





Siemens

3VA2xxx-xMQ3x-0AA0

Format / Size: Hybrid quer

last modified:

11/01/2016