

fixed-mounted molded case circuit breaker frame 1600; with RTC and 4AUX trip alarm switch S24; Icu "M" Icu=55kA @ 415V, 3-pole ETU320, LI, In=1250A rotary coding switch Ir=500...1250A li=1.5...15 x In N conductor protec. adjustable opt. w. ext. CT; up to 200% nut keeper kit No communication connection, no measurement function Motorized operating mechanism 24...30 V AC/DC incl. S21 spring energy store signaling switch With electr. and mech. calling Switch-on solenoid (CC) 24 V AC/DC incl. remote reset solenoid (RR) reset remotely 24 V DC with 2nd auxiliary release UVR, instant Undervoltage 24 V AC/DC without 1st auxiliary release C01= Mechanical switching operations counter MOC K52= Auxiliary current switch AUX 2 CO + 2 CO Variant 2x 400 V AC + 2x 24 V DC K53= Tripped signaling switch S24 as version 24 V DC digital signal

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2712-1AB03-1KB0-Z C01+K52+K53>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2712-1AB03-1KB0-Z C01+K52+K53>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2712-1AB03-1KB0-Z C01+K52+K53

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

2/14/2022

