

fixed-mounted molded case circuit breaker frame 1600; with RTC and 4AUX trip alarm switch S24; Icu "C" Icu=110kA @ 415V, 3-pole ETU350, LSI, In=1250A rotary coding switch Ir=500...1250A Isd=1...10xIn, li=1.5...15xIn N conductor protec. adjustable opt. w. ext. CT; up to 200% straight bus connector extended No communication connection, no measurement function Manual operating mechanism of the spring energy store With mechanical calling without 2nd auxiliary release without 1st auxiliary release

| Model                                                                                                                                        |                             |
|----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                                                           | SENTRON                     |
| product designation                                                                                                                          | Molded case circuit breaker |
| design of the product                                                                                                                        | MCCB                        |
| design of the actuating element                                                                                                              | spring actuator             |
| type of the driving mechanism                                                                                                                | without motor drive         |
| type of the driving mechanism / motor drive                                                                                                  | No                          |
| design of the overcurrent release                                                                                                            | ETU350                      |
| General technical data                                                                                                                       |                             |
| number of poles                                                                                                                              | 3                           |
| size of the circuit-breaker                                                                                                                  | 1600 A                      |
| mechanical service life (operating cycles) / typical                                                                                         | 10 000                      |
| circuit-breaker / Design                                                                                                                     | 3VA2                        |
| Voltage                                                                                                                                      |                             |
| insulation voltage / rated value                                                                                                             | 1 000 V                     |
| operating voltage / at AC / at 50/60 Hz / rated value                                                                                        | 690 V                       |
| protection class IP                                                                                                                          | IP20                        |
| <ul style="list-style-type: none"> <li>protection class IP / on the front</li> <li>protection function of the overcurrent release</li> </ul> | IP20<br>LSI                 |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole                                                  | 47 W                        |
| Auxiliary circuit                                                                                                                            |                             |
| number of CO contacts / for auxiliary contacts                                                                                               | 4                           |
| Suitability                                                                                                                                  |                             |
| suitability for use                                                                                                                          | system protection           |
| Adjustable parameters                                                                                                                        |                             |
| adjustable current response value current / of the current-dependent overload release / initial value                                        | 500 A                       |
| product component                                                                                                                            |                             |
| <ul style="list-style-type: none"> <li>trip indicator</li> <li>voltage trigger</li> <li>undervoltage release</li> </ul>                      | Yes<br>No<br>No             |
| product extension / optional / motor drive                                                                                                   | Yes                         |
| Product function                                                                                                                             |                             |
| product function                                                                                                                             |                             |
| <ul style="list-style-type: none"> <li>grounding protection</li> </ul>                                                                       | No                          |
| Display and operation                                                                                                                        |                             |
| display version                                                                                                                              | Without display             |
| Short circuit                                                                                                                                |                             |
| operating short-circuit current breaking capacity (Ics)                                                                                      |                             |
| <ul style="list-style-type: none"> <li>at 415 V / rated value</li> <li>at 500 V / rated value</li> <li>at 690 V / rated value</li> </ul>     | 110 kA<br>63 kA<br>36 kA    |
| maximum short-circuit current breaking capacity (Icu)                                                                                        |                             |
| <ul style="list-style-type: none"> <li>at 415 V / rated value</li> <li>at 440 V / rated value</li> <li>at 500 V / rated value</li> </ul>     | 110 kA<br>100 kA<br>85 kA   |

- at 690 V / rated value

50 kA

#### Connections

|                                                                 |                                                  |
|-----------------------------------------------------------------|--------------------------------------------------|
| arrangement of electrical connectors / for main current circuit | Main connection at the front, extension enclosed |
| type of electrical connection / for main current circuit        | busbar connection                                |

#### Mechanical Design

|                  |                |
|------------------|----------------|
| height           | 296 mm         |
| width            | 210 mm         |
| depth            | 183 mm         |
| fastening method | fixed mounting |
| net weight       | 14 kg          |

#### Environmental conditions

|                                        |        |
|----------------------------------------|--------|
| ambient temperature / during operation |        |
| • minimum                              | -25 °C |
| • maximum                              | 70 °C  |
| ambient temperature / during storage   |        |
| • minimum                              | -40 °C |
| • maximum                              | 70 °C  |

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2712-3AC05-0AA0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2712-3AC05-0AA0>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2712-3AC05-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2712-3AC05-0AA0)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>

last modified:

6/20/2022 