

fixed-mounted molded case circuit breaker w. handle frame 1600; 4AUX and trip alarm switch S24; Icu "H" Icu=85kA @ 415V, 4-pole, right ETU360, LSIG, In=1250A rotary coding switch Ir=500...1250A Isd=1...10xIn, li=1.5...15xIn N conductor protec. adjustable OFF, 50%, 100%, 200% gr.-fault prot., can be sw. off Ig=0.1...1 x In, tg=0.1...0.8s nut keeper kit No communication connection, no measurement function With trip alarm switch TAS and trip alarm switch S25 With mechanical calling with 2nd auxiliary release UVR, instant Undervoltage 220-240 V AC/DC without 1st auxiliary release

Model	
product brand name	SENTRON
product designation	Molded case circuit breaker
design of the product	MCCB
design of the actuating element	toggel handle actuator
type of the driving mechanism	manual operating mechanism
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU360
General technical data	
number of poles	4
size of the circuit-breaker	1600 A
mechanical service life (switching cycles) / typical	1 000
circuit-breaker / Design	3VA2
Voltage	
insulation voltage / rated value	1 000 V
operating voltage / at AC / at 50/60 Hz / rated value	690 V
protection class IP	IP20
protection class IP / on the front	IP20
protection function of the overcurrent release	LSIG
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	47 W
Current	
operational current	
• at 40 °C / rated value	1 250 A
• at 45 °C / rated value	1 250 A
• at 50 °C / rated value	1 250 A
• at 55 °C / rated value	1 240 A
• at 60 °C / rated value	1 182 A
• at 65 °C / rated value	1 122 A
• at 70 °C / rated value	1 057 A
continuous current / rated value	1 250 A
adjustable current response value current	
• of the current-dependent overload release / full-scale value	1 250 A
• of instantaneous short-circuit trip unit / minimum	1 875 A
• of instantaneous short-circuit trip unit / maximum	18 750 A
short-time withstand current (Icw)	
• limited to 1 s / rated value	20 kA
• at AC / at 415 V / limited to 0.5 s / rated value	20 kA
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	4
Suitability	
suitability for use	system protection
Adjustable parameters	

adjustable current response value current	
• of the short-time delayed short-circuit release / initial value	1 250 A
• of the short-time delayed short-circuit release / full-scale value	12 500 A
adjustable current response value current / of the current-dependent overload release / initial value	500 A
product component	
• trip indicator	Yes
• voltage trigger	No
• undervoltage release	Yes
product extension / optional / motor drive	No
Product function	
product function	
• grounding protection	Yes
Display and operation	
display version	Without display
Short circuit	
breaking capacity operating short-circuit current (Ics)	
• at 415 V / rated value	85 kA
• at 500 V / rated value	55 kA
• at 690 V / rated value	36 kA
breaking capacity maximum short-circuit current (Icu)	
• at 415 V / rated value	85 kA
• at 440 V / rated value	85 kA
• at 500 V / rated value	55 kA
• at 690 V / rated value	36 kA
Connections	
arrangement of electrical connectors / for main current circuit	Main connection on front side
type of electrical connection / for main current circuit	busbar connection
Mechanical Design	
height	296 mm
width	280 mm
depth	183 mm
fastening method	fixed mounting
net weight	16 kg
Environmental conditions	
ambient temperature / during operation	
• minimum	-25 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	70 °C
General Product Approval	
EMC	
Declaration of Conformity	



[Miscellaneous](#)



[UK Declaration of Conformity](#)



EG-Konf.

Test Certificates	Marine / Shipping	other
--------------------------	--------------------------	--------------

[Miscellaneous](#)



[Miscellaneous](#)

other	Dangerous Good
-------	----------------

[Miscellaneous](#)

[Dangerous Goods
Information](#)

[Transport Informa-
tion](#)

Further information

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2712-6AD23-1AH0>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VA2712-6AD23-1AH0>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2712-6AD23-1AH0
CAX-Online-Generator
<http://www.siemens.com/cax>
Tender specifications
<http://www.siemens.com/specifications>



last modified: 4/6/2020

